

MS705 SM

Solid Skid Steer - Construction PRO

Premium three stage solid construction tire.


- Zero maintenance solid construction
 - No flats due to punctures or sidewall damage
 - No need to check air pressure
- Extra deep tread allows for 3 to 5 times longer tire life vs pneumatic
- Ultra wear & cut resistant tread compound
- Heat resistant, cushion center compound
- Smooth (SM) tread available to maximize tire life
- Aperture (AP) sidewall configuration provides softer ride
- Ideal for the most extreme OTR and construction applications



Applications



Footprint



Size	Sidewall	Rim	Load Index	Load Capacity (lbs / kg)		Unit	Tire Dimensions		
				5 mph 10 km/h	10 mph 15 km/h		Tread Depth	Section Width	Overall Diameter
31x10-20 (10-16.5)	ST	7.5x20	152A2	7850	5690	in.	1.7	10.0	31.0
				3550	2575	mm	43	254	787
31x10-20 (10-16.5)	AP	7.5x20	148A2	6950	5030	in.	1.7	10.0	31.0
				3150	2280	mm	43	254	787
33x12-20 (12-16.5)	ST	7.5x20	156A2	8800	6375	in.	2.2	11.0	33.0
				4000	2900	mm	56	279	838
33x12-20 (12-16.5)	AP	7.5x20	152A2	7850	5690	in.	2.2	11.0	33.0
				3550	2575	mm	56	279	838