



MAXAM

MS301

E-3/G-3/L-3

For use on loaders and articulated dump trucks operating in mixed applications.

- Excellent traction in all off-road conditions
- Thick undertread for improved puncture resistance
- High-quality carcass allows for excellent retreadability
- Wear and cut-resistant tread compound
- Wide flat footprint profile for maximum stability and wear
- Increased net-to-gross for improved tread life

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	TRA	L.I.	Infl. P.	Speed	Tire Load
				mm inch	mm inch	mm inch			kPa psi		
17.5R25	**	TL	14.00/1.5	1339 52.7	449 17.7	28 35/32	E-3	167B	525 76	50 30	5450 12000
							G-3	153A8	300 44	40 25	3650 8050
							L-3	182A2	650 94	10 6	8500 18700
20.5R25	**	TL	17.00/2.0	1499 59	517 20.4	30 37/32	E-3	177B	525 76	50 30	7300 16100
							G-3	161A8	300 44	40 25	4625 10200
							L-3	193A2	650 94	10 6	11500 25400
23.5R25	**	TL	19.50/2.5	1611 63.4	608 23.9	33 41/32	E-3	185B	525 76	50 30	9250 20400
							G-3	170A8	300 44	40 25	6000 13200
							L-3	201A2	650 94	10 6	14500 32000
26.5R25	**	TL	22.00/3.0	1748 68.8	679 26.7	36 45/32	E-3	193B	525 76	50 30	11500 25400
							L-3	209A2	650 94	10 6	18500 40800
							E-3	200B	525 76	50 30	14000 30900
29.5R25	**	TL	25.00/3.5	1886 74.3	763 30	39 49/32	E-3	200B	525 76	50 30	14000 30900
							L-3	216A2	650 94	10 6	22400 49400
							E-3	200B	525 76	50 30	14000 30900

