



MAXAM MS501

MINEXTRA

L-5

For use in the most severe applications where traction and long tread life are required.

- Specialized mining compound for increased cut and impact resistance
- Extra deep L-5 offset lug pattern combines excellent traction and high resistance to wear in all off-road conditions
- Deep undertread for improved puncture resistance
- Reinforced bead, shoulder, and sidewall for increased cut resistance

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	TRA	L.I.	Infl. P.	Speed	Tire Load
				mm inch	mm inch	mm inch			kPa psi	km/h mph	kg lbs
17.5R25	**	TL	14.00/1.5	1395	445	66	L-5	182A2	650	10	8500
				54.9	17.5	83/32			94	6	18700
20.5R25	**	TL	17.00/2.0	1548	531	72	L-5	193A2	650	10	11500
				60.9	20.9	90/32			94	6	25400
23.5R25	**	TL	19.50/2.5	1665	605	78	L-5	201A2	650	10	14500
				65.6	23.8	98/32			94	6	32000
26.5R25	**	TL	22.00/3.0	1794	684	87	L-5	209A2	650	10	18500
				70.6	26.9	110/32			94	6	40800
29.5R25	**	TL	25.00/3.5	1920	777	94	L-5	216A2	650	10	22400
				75.6	30.6	118/32			94	6	49400
29.5R29	**	TL	25.00/3.5	2010	800	99	L-5	218A2	650	10	23600
				79.1	31.5	125/32			94	6	52000
35/65R33	**	TL	25.00/3.5	2085	914	95	L-5	224A2	650	10	28000
				82.1	36	120/32			94	6	61500

