



MAXAM

MS503

L-5T

The non-directional L-5T radial tire designed to provide high level of stability and traction

- The aggressive, open tread pattern provides grip and traction
- The staggered tread blocks combine to give operators continuous ground contact for a better riding comfort
- Square-shouldered design provides excellent stability and protection from cuts

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	TRA	L.I.	Infl. P.	Speed	Tire Load
				mm inch	mm inch	mm inch			kPa psi	km/h mph	kg lbs
17.5R25	**	TL	14.00/1.5	1401	440	65	L-5T	182A2	650	10	8500
				55.2	17.3	82/32			94	6	18700
20.5R25	**	TL	17.00/2.0	1554	542	70	L-5T	193A2	650	10	11500
				61.2	21.3	88/32			94	6	25400
23.5R25	**	TL	19.50/2.5	1668	610	79	L-5T	201A2	650	10	14500
				65.7	24	99/32			94	6	32000
26.5R25	**	TL	22.00/3.0	1798	683	87	L-5T	209A2	650	10	18500
				70.8	26.9	110/32			94	6	40800
29.5R25	**	TL	25.00/3.5	1911	773	96	L-5T	216A2	650	10	22400
				75.2	30.4	121/32			94	6	49400
29.5R25	**	TL	25.00/3.5	1920	777	97	L-5S	216A2	650	10	22400
				75.6	30.6	122/32			94	6	49400

