



MAXAM

MS903

BACKHOE INDUSTRIAL SERVICE

Modified R4 tread pattern for excellent traction and flotation in soft underfoot conditions.

- Tread design optimized with self-cleaning mud breakers
- Deep undertread for improved puncture resistance
- Wear and cut resistant compound

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	L.I.	Infl. P.	Load Capacity (kg/lbs)	
				mm inch	mm inch	mm inch			kPa psi	10 km/h 5 mph
18.4-26 (480/80-26)	12	TL	W16L	1430	478	29	156A8		5000	4000
				56.3	18.8	36/32			36	11000
	16	TL	W16L	1430	478	29	162A8		5940	4750
				56.3	18.8	36/32			45	13125
16.9-28 (440/80-28)	12	TL	W15L	1410	437	27	152A8		4440	3550
				55.5	17.2	34/32			38	9815
	14	TL	W15L	1410	437	27	155A8		4840	3875
				55.5	17.2	34/32			44	10690
16.9-30 (420/85-30)	12	TL	W15L	1461	434	27	153A8		4560	3650
				57.5	17.1	34/32			34	10060
	14	TL	W15L	1461	434	27	156A8		5000	4000
				57.5	17.1	34/32			45	11000
18.4-30 (460/85-30)	12	TL	W16L	1529	470	29	158A8		5310	4250
				60.2	18.5	36/32			36	11690
	14	TL	W16L	1529	470	29	160A8		5625	4500
				60.2	18.5	36/32			42	12375

