

MAXAM

MS906

SKID STEER

Deep R4 tread pattern designed for skid steer, backhoe and telehandler applications.

- Full flat profile with self-cleaning stepped tread improves performance
- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces chunking

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	L.I.	Infl. P.	Load Capacity (kg/lbs)
				mm inch	mm inch	mm inch		kPa psi	10 km/h 5 mph
5.70-12	6	TL	4.50	569 22.4	145 5.7	14.0 18/32	93A2	415 60	650 1430
23x8.50-12	6	TL	7JA	583 22.9	214 8.5	13.3 17/32	101A2	340 50	825 1820
				583 22.9	214 8.5	13.3 17/32		450 65	975 2150
	8	TL	7JA	583 22.9	214 8.5	13.3 17/32	115A2	515 75	1215 2680
27x8.50-15	8	TL	7JA	682 26.9	221 8.7	14.0 18/32	118A2	415 60	1320 2910
27x10-12	14	TL	8.00G	701 27.6	264 10.4	19.0 24/32	143A5	690 100	2725 7800
7.00-15	6	TL	5.50	760 29.9	198 7.8	16.0 21/32	121A2	415 60	1450 3200
				760 29.9	198 7.8	16.0 21/32		480 70	1650 3640
31x15.50-15	8	TL	13LB	787.0 31.0	384 15.1	23.0 30/32	132A2	310 45	2000 4400
				768 30.2	271 10.7	16.0 21/32		515 75	2120 4680
10-16.5	10	TL	8.25	768 30.2	271 10.7	16.0 21/32	134A2	515 75	2120 4680
12-16.5	12	TL	9.75	834 32.8	331 13.0	20.0 25/32	145A2	550 80	2900 6400
14-17.5	14	TL	10.50	920 36.2	360 14.2	26.0 33/32	155A2	550 80	3875 8550
15-19.5	14	TL	11.75	1020 40.2	389 15.3	26.0 33/32	161A2	480 70	4625 10200
				1020 40.2	389 15.3	26.0 33/32		550 80	5000 11000

