



MAXAM

MS907

L5 SKID STEER AND BACKHOE

Extra deep, aggressive L5 tread pattern designed for skid steer, backhoe and telehandler applications.

- Full flat profile with self-cleaning stepped tread improves performance
- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces chunking
- Increased net-to-gross for maximum tread life and lowest cost per hour

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	L.I.	Infl. P.	Load Capacity (kg/lbs)
				mm inch	mm inch	mm inch		kPa psi	10 km/h 5 mph
23x8.50-12	8	TL	7JA	574.0	213	28.0	107A2	450	975
				22.6	8.4	35/32		65	2150
27x8.50-15	10	TL	7JA	686.0	221	30.0	122A2	515	1500
				27.0	8.7	38/32		75	3300
10-16.5	14	TL	8.25	795.0	278	35.0	128A2	620	1800
				31.3	10.9	44/32		90	3960
12-16.5	14	TL	9.75	842.0	330	35.0	147A2	620	3075
				33.1	13.0	44/32		90	6800
14-17.5	16	TL	10.50	935.0	357	36.0	157A2	620	4125
				36.8	14.1	46/32		90	9100
12.5/80-18	14	TL	11.00	965	306	37	145A8	425	2900
				38.0	12.0	47/32		62	8260
16.9-28	16	TL	11.00	965	306	37	148A8	480	3150
				38.0	12.0	47/32		70	8940
16.9-28	14	TL	W15L	1410	450	38	155A8	310	3875
				55.5	17.7	48/32		45	10690

