



MAXAM

MS909

MULTIPURPOSE

For use on wheeled excavators where traction and stability are required.

- Wide and open tread design for maximum flotation and traction on soft terrain
- Reinforced sidewall for excellent stability and cut resistance
- Center tie bar reduces vibration during over-the-road driving
- Cut and wear resistant tread compound

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	L.I.	Infl. P.	Load Capacity
				mm inch	mm inch	mm inch		kPa psi	10 km/h 5 mph
405/70-20 (16/70-20)	12	TL	13.00	1077	411	33	145B	320	2900
				42.4	16.2	42/32		46	6400
	14	TL	13.00	1077	411	33	149B	350	3250
405/70-24 (16/70-24)	16	TL	13.00	1077	411	33	152B	400	3550
				42.4	16.2	42/32		58	7850
	14	TL	13.00	1173	404	33	152B	400	3550
445/65-19.5 (18-19.5)	16	TL	14.00	1095	457	27	160B	585	4500
				43.1	18.0	34/32		85	9900
	18	TL	14.00	1095	457	27	164B	690	5000
445/65-22.5 (18-22.5)	16	TL	14.00	1171	457	29	163B	585	4875
				46.1	18.0	36/32		85	10700
	18	TL	14.00	1171	457	29	167B	690	5450
				46.1	18.0	36/32		100	12000

