



MAXAM

MS202

E2/G2/L2

For loaders, graders, telehandlers, and articulated dump trucks operating in soft underfoot conditions. Ideal for use in dirt, mud, snow, and ice.

- Siped block pattern for maximum traction
- Wear and cut-resistant tread compound
- Self-cleaning tread with stone ejectors

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	psi KPa	30 mph 50 kph	
14.00R24	★	TL	10.00VA	53.5	15.3	29	80	15200	69	9100	175A2/157B
				1359	388	23	550	6900	475	4125	
17.5R25	★★	TL	14.00/1.5	52.7	17.7	35	94	18700	76	12000	182A2/167B
				1339	449	28	650	8500	525	5450	
20.5R25	★★	TL	17.00/2.0	58.7	20.3	37	94	25400	76	16100	193A2/177B
				1491	516	30	650	11500	525	7300	
23.5R25	★★	TL	19.50/2.5	63.5	23.5	41	94	32000	76	20400	201A2/185B
				1613	596	33	650	14500	525	9250	
26.5R25	★★	TL	22.00/3.0	68.8	26.7	45	94	40800	76	25400	209A2/193B
				1748	679	36	650	18500	525	11500	

