



MAXAM

MS302

E3/L3

Heavy duty E3/L3+ lug pattern combines excellent traction and high resistance to wear and cutting. Specifically designed to minimize vibration at haul speeds, and provides the lowest cost-per-hour.

- Excellent traction in all off-road conditions
- Thick undertread for improved puncture resistance
- High quality casing allows for excellent retreadability
- Wear and cut resistant tread compound
- Wide, flat footprint profile for maximum stability and wear
- Increased net-to-gross and tread depth for highest tread life
- Offset, reinforced lugs minimize vibration at haul speeds

Applications:



| Size | Rating | Type | Rim | O.D. | S.W | T.D. | Infl. P. | L.C.C. (lbs/kg) | Infl. P. | L.C.C. (lbs/kg) | L.I. |
|-----------|--------|------|-----------|----------|----------|-------------|------------|--------------------|------------|--------------------|------------|
| | | | | in mm | in mm | 32nds mm | psi KPa | 5 mph 10 kph | psi KPa | 30 mph 50 kph | |
| 23.5R25 | ★★ | TL | 19.50/2.5 | 63.5 | 23.6 | 48 | 94 | 32000 | 76 | 20400 | 201A2/185B |
| | | | | 1613 | 599 | 38 | 650 | 14500 | 525 | 9250 | |
| 26.5R25 | ★★ | TL | 22.00/3.0 | 68.6 | 26.5 | 52 | 94 | 40800 | 76 | 25400 | 209A2/193B |
| | | | | 1742 | 672 | 41 | 650 | 18500 | 525 | 11500 | |
| 29.5R25 | ★★ | TL | 25.00/3.5 | 74.5 | 30.0 | 54 | 94 | 49400 | 76 | 30900 | 216A2/200B |
| | | | | 1893 | 763 | 43 | 650 | 22400 | 525 | 14000 | |
| 650/65R25 | ★★ | TL | 19.50/2.5 | 58.2 | 25.0 | 46 | 91 | 30900 | 91 | 17600 | 200A2/180B |
| | | | | 1479 | 636 | 37 | 625 | 14000 | 475 | 8000 | |
| 750/65R25 | ★★ | TL | 24.00/3.0 | 63.3 | 29.4 | 52 | 91 | 40800 | 69 | 23400 | 209A2/190B |
| | | | | 1608 | 747 | 41 | 625 | 18500 | 475 | 10600 | |
| 775/65R29 | ★★ | TL | 25.00/3.5 | 68.5 | 30.5 | 54 | 91 | 45400 | 91 | 26800 | 213A2/195B |
| | | | | 1740 | 775 | 43 | 625 | 20600 | 475 | 12150 | |
| 875/65R29 | ★★ | TL | 27.00/3.5 | 73.4 | 33.5 | 60 | 91 | 56800 | 91 | 34200 | 221A2/203B |
| | | | | 1865 | 851 | 48 | 625 | 25750 | 625 | 15500 | |

