



MAXAM

MS405

DUMPXTRA E4/L4

Deep E4/L4 lug pattern combines excellent traction and high resistance to wear and cutting. Specifically designed to minimize vibration at haul speeds, and provides the lowest cost-per-hour.

- Excellent traction in all off-road conditions
- Deep undertread for improved puncture resistance
- High quality casing allows for excellent retreadability
- Wear and cut resistant tread compound
- Wide, flat footprint profile for maximum stability and wear

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	psi KPa	30 mph 50 kph	
23.5R25	★★	TL	19.50/2.5	63.7	23.8	68	94	32000	76	20400	201A2/185B
				1617	605	54	650	14500	525	9250	
26.5R25	★★	TL	22.00/3.0	68.5	27.0	75	94	40800	76	25400	209A2/193B
				1739	687	60	650	18500	525	11500	
29.5R25	★★	TL	25.00/3.5	73.5	30.2	79	94	49400	76	30900	216A2/200B
				1868	767	63	650	22400	525	14000	
875/65R29	★★	TL	27.00/3.5	73.6	34.0	75	91	56800	69	34200	221A2/203B
				1868	864	60	625	25750	475	15500	

