



MAXAM

MS406

E4/L4

Deep E4/L4 lug pattern combines excellent traction and high resistance to wear and cutting. Specifically designed to maximize traction in loader applications, and provides the lowest cost-per-hour.

- Excellent traction in all off-road conditions
- Deep undertread for improved puncture resistance
- High quality casing allows for excellent retreadability
- Wear and cut resistant tread compound
- Wide, flat footprint profile for maximum stability and wear

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in	in	32nds	psi	5 mph	psi	30 mph	
				mm	mm	mm	KPa	10 kph	KPa	50 kph	
23.5R25	★★	TL	25.00/3.5	65.0	24.1	66	94	32000	76	20400	201A2/185B
				1651	610	52	650	14500	525	9250	
26.5R25	★★	TL	25.00/3.5	69.2	26.8	71	94	40800	76	25400	209A2/193B
				1757	680	56	650	18500	525	11500	
29.5R25	★★	TL	25.00/3.5	74.8	30.3	76	94	49400	76	30900	216A2/200B
				1900	770	60	650	22400	525	14000	
29.5R29	★★	TL	25.00/3.5	78.9	30.2	76	94	52000	76	33100	218A2/202B
				2005	766	60	650	23600	525	15000	
35/65R33	★★	TL	28.00/3.5	81.3	34.5	83	94	61500	76	38600	224A2/207B
				2066	877	66	650	28000	525	17500	

