



MAXAM

MS502

MINEXTRA - L5S

For equipment operating in highly abrasive material environments where maximum protection from penetrations and cuts is needed.

- Extra deep L5S design provides highest resistance to wear and cutting, improving tire life and lowering operating cost
- Deep undertread for improved puncture resistance
- Reinforced bead, shoulder, and sidewall for increased cut resistance
- Specialized mining compound for increased cut and impact resistance

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	
18.00R25	★★	TL	13.00/2.5	65.7	20.1	110	120	35300	204A2
				1670	511	87	825	16000	
17.5R25	★★	TL	14.00/1.5	54.9	17.5	86	94	18700	182A2
				1395	445	68	650	8500	
20.5R25	★★	TL	17.00/2.0	60.9	20.9	93	94	25400	193A2
				1548	531	74	650	11500	
23.5R25	★★	TL	19.50/2.5	65.6	23.8	101	94	32000	201A2
				1665	605	80	650	14500	
26.5R25	★★	TL	22.00/3.0	70.6	26.9	113	94	40800	209A2
				1794	684	90	650	18500	
29.5R25	★★	TL	25.00/3.5	75.6	30.6	122	94	49400	216A2
				1920	777	97	650	22400	
29.5R29	★★	TL	25.00/3.5	79.1	31.5	129	94	52000	218A2
				2010	800	102	650	23600	

