



**MAXAM**

# MS503

**L5T**

Extra deep, open lug L5T traction pattern combines excellent traction and high resistance to wear and cutting. Specifically designed to maximize service life in the harshest applications.

- Excellent traction in all off-road conditions
- Staggered tread blocks provide continuous ground contact for improved ride comfort
- Reinforced bead, shoulder, and sidewall construction
- Square shoulder design and wide footprint maximizes stability
- Stone and mud ejectors prevent debris buildup between lugs

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	
17.5R25	★★	TL	14.00/1.5	55.2	17.3	82	94	18700	182A2
				1401	440	65	650	8500	
20.5R25	★★	TL	17.00/2.0	61.2	21.3	88	94	25400	193A2
				1554	542	70	650	11500	
23.5R25	★★	TL	19.50/2.5	65.7	24.0	99	94	32000	201A2
				1668	610	79	650	14500	
26.5R25	★★	TL	22.00/3.0	70.8	26.9	110	94	40800	209A2
				1798	683	87	650	18500	
29.5R25	★★	TL	25.00/3.5	75.2	30.4	121	94	49400	216A2
				1911	773	96	650	22400	
35/65R33	★★	TL	28.00/3.5	81.3	35.5	125	94	61500	224A2
				2064	901	99	650	28000	

