



**MAXAM**

# MS701 GSE

## GROUND SUPPORT EQUIPMENT

For use in Ground Support, industrial and manufacturing applications.

- Extra deep ribs provide exceptional grip in wet conditions
- Reduced vibration and improved stability
- Cool running cushion center compound
- Low rolling resistance tread compound
- Optional apertures for extra soft ride

Applications:



Size	Alt. Size	Rim	Sidewall	O.D.		S.W.		L.C.C (lbs/kg)	
				in.	mm	in.	mm	6 mph/10 kph	10 mph/15 kph
4.00-8	4.80-8	3.00D	ST	16.0	406	4.6	117	2320/1050	1685/765
			AP	16.0	406	4.6	117	1970/895	1430/650
		3.75I	ST	16.0	406	4.6	117	2910/1320	2105/955
			AP	16.0	406	4.6	117	2470/1120	1800/815
5.00-8	5.70-8	3.75I	ST	17.8	452	5.3	135	3330/1510	2420/1100
			AP	17.8	452	5.3	135	2840/1290	2060/935
		4.25I	ST	17.8	452	5.3	135	3660/1660	2660/1205
			AP	17.8	452	5.3	135	3110/1410	2330/1055
		4.50K	ST	17.8	452	5.3	135	4010/1820	2905/1320
			AP	17.8	452	5.3	135	3410/1545	2470/1120

