



MAXAM

MS801

INDUSTRIAL PNEUMATICS

Designed for use in multiple applications, the MS801 offers excellent traction and protection from punctures, as well as improved stability.

- Extra wide profile and reinforced sidewall for improved stability
- Thick undertread for maximum puncture resistance
- Self-cleaning industrial tread design provides excellent traction
- Cut and wear resistant compound

Applications:



Size	P.R.	Type	Rim	O.D.		S.W.		T.D.		Infl. P.	L.C.C (lbs/kg)	
				in.	mm	in	mm	32nds	mm		psi/KPa	15 mph/25 kph
											Load Wheels	Steer Wheels
18x7-8	14	TT	4.33R	18.3	465	6.8	173	21	17	130/900	3990/1810	3195/1450
	16	TT	4.33R	18.3	465	6.8	173	21	17	145/1000	4540/2060	3640/1650
5.00-8	10	TT	3.00D	18.4	467	5.4	137	18	14	145/1000	3000/1360	2400/1090
6.00-9	10	TT	4.00	21.5	546	6.5	165	20	16	123/850	3640/1650	2910/1320
	12	TT	4.00	21.5	546	6.5	165	20	16	145/1000	3990/1810	3195/1450
23x9-10	18	TT	6.50F	23.0	584	9.0	229	24	19	130/900	6690/3035	5355/2430
	20	TT	6.50F	23.0	584	9.0	229	24	19	145/1000	7300/3310	5840/2650
6.50-10	10	TT	5.00	23.4	594	7.0	178	21	17	112/775	4135/1875	3305/1500
	12	TT	5.00	23.4	594	7.0	178	21	17	140/970	4510/2045	3605/1635
23x10-12	16	TT	8.00G	23.5	597	9.6	244	25	20	115/800	6690/3035	5355/2430
	20	TT	8.00G	23.5	597	9.6	244	25	20	145/1000	7990/3625	6395/2900
7.00-12	12	TT	5.00	26.7	678	7.7	196	22	17	123/850	5675/2575	4540/2060
	14	TT	5.00	26.7	678	7.7	196	22	17	130/900	5840/2650	4675/2120
27x10-12	16	TT	8.00G	26.9	683	10.0	254	29	23	115/800	8265/3750	6610/3000
	18	TT	8.00G	26.9	683	10.0	254	29	23	130/900	8950/4060	7165/3250
8.15-15 (28x9-15)	20	TT	8.00G	26.9	683	10.0	254	29	23	145/1000	9775/4435	4825/3550
	14	TT	7.00	27.9	709	8.7	221	23	18	145/1000	8265/3750	6610/3000
250-15	18	TT	7.50BD	28.9	734	9.8	249	25	20	138/950	1055/4560	8045/3650
	20	TT	7.50BD	28.9	734	9.8	249	25	20	145/1000	10680/4845	8540/3875
7.00-15	14	TT	5.50BD	30.0	762	8.4	213	25	20	135/930	7100/3220	5675/2575
7.50-15	14	TT	6.00BD	32.0	813	8.7	221	25	20	135/930	7715/3500	6175/2800
8.25-15	14	TT	6.50	33.4	848	9.6	244	24	19	115/800	8950/4060	7165/3250
300-15	20	TT	8.00	33.2	843	11.7	297	30	24	130/900	13780/6250	11025/5000
	22	TT	8.00	33.2	843	11.7	297	30	24	145/1000	14185/6435	11355/5150
9.00-20	14	TT	7.00	40.9	1039	10.3	262	38	30	130/900	12400/5625	9920/4500
10.00-20	16	TT	7.50	42.4	1077	11.2	284	43	34	130/900	13780/6250	11025/5000
11.00-20	18	TT	8.00	43.6	1107	11.7	297	45	36	145/1000	16535/7500	13225/6000
12.00-20	24	TT	8.50	45.3	1150	12.5	317	48	38	145/1000	19565/8875	15650/7100
	28	TT	8.50	45.3	1150	12.5	317	48	38	150/1030	20120/9125	16095/7300
12.00-24	20	TT	8.50	49.2	1249	12.5	317	48	38	145/1000	26875/12190	21495/9750
14.00-24	28	TT	10.00W	53.9	1369	14.8	376	52	41	150/1030	27560/12500	22045/10000