



MAXAM

MS907

L5 SKID STEER AND BACKHOE

Extra deep, aggressive L5 tread pattern designed for skid steer, backhoe and telehandler applications.

- Full flat profile with self-cleaning stepped tread improves performance
- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces chunking
- Increased net-to-gross for maximum tread life and lowest cost per hour

Applications:



Size	P.R.	Type	Rim	O.D.	S.W	T.D.	Inf. P.	L.C.C. (lbs/kg)
				in mm	in. mm	32nds mm	psi KPa	5 mph 10 kph
23x8.50-12	8	TL	7JA	22.6	8.4	35	65	2150
				574	213	28	450	975
27x8.50-15	10	TL	7JA	27.0	8.7	38	75	3300
				686	221	30	515	1500
10-16.5	14	TL	8.25	31.3	10.9	44	105	5680
				795	278	35	620	1800
12-16.5	14	TL	9.75	33.1	13.0	44	90	6780
				842	330	35	620	3075
14-17.5	16	TL	10.50	36.8	14.1	46	90	9100
				935	357	36	620	4125
12.5/80-18	14	TL	W9	38.0	12.0	47	62	8260
				965	306	37	425	3745
	16	TL	W9	38.0	12.0	47	70	8940
				965	306	37	480	4055
16.9-28	14	TL	W15L	55.5	17.7	48	45	10690
				1410	450	38	310	4850

