



MAXAM

MS908

WHEELED EXCAVATOR

For use on wheeled excavators where traction and stability are required.

- Self-cleaning open tread with mud breakers provides improved traction
- Reinforced sidewall for excellent stability and cut resistance
- Centerline tread tie bars reduces vibration during over-the-road driving

Applications:



| Size | P.R. | Type | Rim | O.D. | S.W | T.D. | Inf. P. | L.C.C. (lbs/kg) | | L.I. |
|----------|------|------|------|----------|-----------|-------------|---------|-----------------|-----------------|------|
| | | | | in mm | in. mm | 32nds mm | | psi KPa | 5 mph 10 kph | |
| 8.25-20 | 14 | TT | 6.50 | 37.4 | 8.8 | 24 | 105 | 7640 | 4940 | 136B |
| | | | | 950 | 224 | 19 | 720 | 3460 | 2240 | |
| 9.00-20 | 14 | TT | 7.00 | 39.6 | 9.9 | 25 | 102 | 8540 | 5520 | 140B |
| | | | | 1006 | 251 | 20 | 700 | 3865 | 2500 | |
| 10.00-20 | 16 | TT | 7.50 | 41.4 | 10.8 | 26 | 108 | 10740 | 6950 | 148B |
| | | | | 1052 | 274 | 21 | 740 | 4875 | 3150 | |
| 11.00-20 | 16 | TT | 8.00 | 42.0 | 11.0 | 28 | 105 | 11450 | 7400 | 150B |
| | | | | 1067 | 279 | 22 | 720 | 5180 | 3350 | |

