



MAXAM

MS708

OTR PRO

Applications:



Engineered for wheeled loaders operating in the most severe waste, recycling, and mining applications.

- Low durometer center compound, combined with patented “Double D” apertures provide excellent ride vs 2-stage products
- True 3-stage all rubber design for reduced heat generation and high cut resistance
- Zero maintenance and downtime for maximum productivity
- Available in smooth or traction tread designs for maximum versatility in all applications
- Mounts on standard multi-piece earthmover rims

| Size | Tread | Sidewall | Rim | O.D. | S.W | T.D. | L.C.C. (lbs/kg) | | L.I. |
|---------|-------|----------|-------|----------|----------|----------|-----------------|------------------|-------|
| | | | | in mm | in mm | in mm | 5 mph 10 kph | 10 mph 15 kph | |
| 17.5-25 | SM | ST | 14.00 | 53.0 | 17.8 | 6.1 | 24700 | 17890 | 192A2 |
| | | AP | | 1346 | 452 | 155 | 11200 | 8100 | 188A2 |
| | | | | 53.0 | 17.8 | 6.1 | 22230 | 16100 | |
| | TR | ST | 14.00 | 53.0 | 17.8 | 6.1 | 24700 | 17890 | 192A2 |
| | | AP | | 1346 | 452 | 155 | 10090 | 7300 | 188A2 |
| | | | | 53.0 | 17.8 | 6.1 | 22230 | 16100 | |
| 20.5-25 | SM | ST | 17.00 | 58.8 | 20.8 | 7.4 | 35300 | 25570 | 204A2 |
| | | AP | | 1493 | 528 | 188 | 16010 | 11600 | 200A2 |
| | | | | 58.8 | 20.8 | 7.4 | 30900 | 22380 | |
| | TR | ST | 17.00 | 58.8 | 20.8 | 7.4 | 35300 | 25570 | 204A2 |
| | | AP | | 1493 | 528 | 188 | 14020 | 10150 | 200A2 |
| | | | | 58.8 | 20.8 | 7.4 | 30900 | 22380 | |
| 23.5-25 | SM | ST | 19.50 | 64.0 | 23.5 | 8.6 | 44100 | 31950 | 212A2 |
| | | AP | | 1625 | 597 | 218 | 20000 | 14500 | 208A2 |
| | | | | 64.0 | 23.5 | 8.6 | 39700 | 28760 | |
| | TR | ST | 19.50 | 64.0 | 23.5 | 8.6 | 44100 | 31950 | 212A2 |
| | | AP | | 1625 | 597 | 218 | 20000 | 14500 | 208A2 |
| | | | | 64.0 | 23.5 | 8.6 | 39700 | 28760 | |
| 26.5-25 | SM | ST | 22.00 | 68.4 | 27.0 | 9.5 | 53600 | 38830 | 219A2 |
| | | AP | | 1737 | 686 | 241 | 24300 | 17600 | 215A2 |
| | | | | 68.4 | 27.0 | 9.5 | 48100 | 34840 | |
| | TR | ST | 22.00 | 68.4 | 27.0 | 9.5 | 53600 | 38830 | 219A2 |
| | | AP | | 1737 | 686 | 241 | 21800 | 15800 | 215A2 |
| | | | | 68.4 | 27.0 | 9.5 | 48100 | 34840 | |
| 29.5-25 | SM | ST | 25.00 | 73.0 | 29.7 | 10.4 | 66000 | 47810 | 226A2 |
| | | AP | | 1854 | 754 | 264 | 30000 | 21700 | 222A2 |
| | | | | 73.0 | 29.7 | 10.4 | 58400 | 42305 | |
| | TR | ST | 25.00 | 73.0 | 29.7 | 10.4 | 66000 | 47810 | 226A2 |
| | | AP | | 1854 | 754 | 264 | 26500 | 19190 | 222A2 |
| | | | | 73.0 | 29.7 | 10.4 | 58400 | 42305 | |
| | | | | 1854 | 754 | 264 | 26500 | 19190 | |