



MAXAM

MS931

LOGXTRA - LS2 FORESTRY

Designed for use on demanding forestry equipment. High strength, belt stabilized tire construction provides excellent traction and flotation in severe logging applications.

- Heavy duty shoulder and sidewall
- Maximum protection from cuts, impact, and punctures
- Cut resistant compound specifically engineering for forestry service
- Steel reinforced undertread

Applications:



Size	PR	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	20 mph 30 kph	
23.1-26	16	TL	DW20B	63.8	22.8	72	35	9900	160A6
				1620	580	58	240	4500	
28L-26	16	TL	DW25B	63.9	28.0	76	30	10500	162A6
				1624	710	60	205	4750	
	20	TL	DW25B	64.1	27.8	76	35	11400	165A6
			1628	707	60	240	5150		
24.5-32	20	TL	DH21	72.1	24.5	75	40	13200	170A6
				1831	622	60	275	6000	
30.5L-32	20	TL	DH27	73.0	30.3	82	30	13200	170A6
				1855	769	65	205	6000	
	26	TL	DH27	73.0	30.2	82	40	15700	176A6
				1855	768	65	275	7100	
35.5L-32	20	TL	DH31	79.2	35.5	84	25	16100	177A6
				2011	902	67	175	7300	
	26	TL	DH31	79.2	35.5	84	35	19300	183A6
			2011	902	67	240	8750		

