



# MAXAM

## MS701 SM

### INDUSTRIAL PRO



Premium 3-stage solid resilient tire.

- Smooth tread pattern for maximum tread life
- Premium natural rubber compounds:
  - Compounds do not contain crumb rubber or other fill materials
  - Cut and tear resistant tread
  - Chunk resistant non-marking (NM)
  - Soft, heat resistant cushion center
  - Pure rubber base compound
- Premium 3-stage compound construction:
  - Evenly layered compound uniformity
  - Internal steel ring reinforcement eliminates wheel slip
- Product conforms to TRA and ETRTO global design standards
- Wide footprint for maximum lifting stability
- Full tread profile for uniform load distribution
- Available in both Standard and Swift (Clip/Halo/LOC) bead set configuration

Applications:



Size	Rim	Type		O.D.		S.W.		T.D.		L.C.C. (lbs/kg)	
		STD	SWIFT	in.	mm	in.	mm	in.	mm	15 mph/25 kph Load Wheels	Steer Wheels
18x9-8 SM	7.00	*	*	18.1	460	8.4	213	1.6	41	5590/2535	4300/1950
6.00-9 SM	4.00E	*	*	20.6	523	5.4	137	1.7	43	4155/1885	3200/1450
6.50-10 SM	5.00F	*	*	22.3	566	6.4	163	2.0	51	5160/2340	3970/1800
7.00-12 SM	5.00S	*	*	25.7	653	6.8	173	2.2	56	6440/2920	4940/2240
28x9-15 (8.15-15) SM	7.00	*	*	27.0	686	8.6	218	2.0	51	8600/3900	6610/3000
8.25-15 SM	6.50	*	*	32.0	813	8.3	211	2.8	71	10470/4750	8050/3650
10.00-20 SM	7.50	*		40.7	1034	10.0	254	3.2	81	13230/6000	11025/5000
	8.00	*		40.7	1034	10.0	254	3.2	81	13230/6000	11025/5000
12.00-20 SM	8.00	*		42.8	1087	11.3	287	3.4	86	16660/7560	13890/6300
	8.50	*		42.8	1087	11.3	287	3.4	86	16660/7560	13890/6300
	10.00	*		42.8	1087	11.3	287	3.4	86	17190/7800	14330/6500