



MAXAM MS904

BACKHOE - INDUSTRIAL SERVICE

Modified R4 tread pattern for applications combining high off-road traction and excellent on road performance.

- Tread design optimized with self-cleaning mud breakers
- Center tie bar reduces vibration during over-the-road driving
- Deep undertread for improved puncture resistance
- Wear and cut resistant compound
- Increased net-to-gross for long tread life

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)		L.I.
				in mm	in. mm	32nds mm		psi KPa	5 mph 10 kph	
17.5L-24 (460/70-24)	10	TL	W15L	48.8	17.5	33	32	7690	6150	144A8
				1240	445	26	220	3500	2800	
	12	TL	W15L	48.8	17.5	33	38	8940	7150	149A8
				1240	445	26	26	4060	3250	
	16	TL	W15L	48.8	17.5	33	46	11000	8800	156A8
				1240	445	26	320	5000	4000	
19.5L-24 (500/70-24)	12	TL	W16L	51.7	19.5	34	33	9500	7600	151A8
				1313	495	28	225	4310	3450	
	16	TL	W16L	51.7	19.5	34	42	11375	9100	157A8
				1313	495	28	290	5150	4125	
21L-24	12	TL	W18	53.3	20.0	35	32	10690	8550	155A8
				1354	508	28	220	4840	3875	

