



MAXAM MS907

L5 SKID STEER AND BACKHOE

Extra deep, aggressive L5 tread pattern designed for skid steer, backhoe and telehandler applications.

- Full, flat profile with self-cleaning stepped tread improves performance
- Center tie bar reduces vibration during over-the-road driving
- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces tread chunking
- Increased net-to-gross for maximum tread life and lowest cost per hour

Applications:



| Size | P.R. | Type | Rim | O.D. | S.W. | T.D. | Infl. P. | L.C.C. (lbs/kg) |
|------------|------|------|-------|----------|-----------|-------------|------------|-----------------|
| | | | | in mm | in. mm | 32nds mm | psi KPa | 5 mph 10 kph |
| 23x8.50-12 | 8 | TL | 7JA | 22.6 | 8.4 | 35 | 65 | 2150 |
| | | | | 574 | 213 | 28 | 450 | 975 |
| 27x8.50-15 | 10 | TL | 7JA | 27.0 | 8.7 | 38 | 75 | 3300 |
| | | | | 686 | 221 | 30 | 515 | 1500 |
| 10-16.5 | 14 | TL | 8.25 | 31.3 | 10.9 | 44 | 105 | 5680 |
| | | | | 795 | 278 | 35 | 620 | 1800 |
| 12-16.5 | 14 | TL | 9.75 | 33.1 | 13.0 | 44 | 90 | 6780 |
| | | | | 842 | 330 | 35 | 620 | 3075 |
| 14-17.5 | 16 | TL | 10.50 | 36.8 | 14.1 | 46 | 90 | 9100 |
| | | | | 935 | 357 | 36 | 620 | 4125 |
| 12.5/80-18 | 14 | TL | W9 | 38.0 | 12.0 | 47 | 62 | 8260 |
| | | | | 965 | 306 | 37 | 425 | 3745 |
| | 16 | TL | W9 | 38.0 | 12.0 | 47 | 70 | 8940 |
| | | | | 965 | 306 | 37 | 480 | 4055 |
| 19.5L-24 | 14 | TL | W16L | 51.1 | 19.3 | 48 | 38 | 10310 |
| | | | | 1298 | 490 | 38 | 265 | 4680 |
| 21L-24 | 16 | TL | W18 | 54.1 | 20.6 | 50 | 40 | 12375 |
| | | | | 1374 | 523 | 40 | 275 | 5615 |
| 16.9-28 | 14 | TL | W15L | 55.5 | 17.7 | 48 | 45 | 10690 |
| | | | | 1410 | 450 | 38 | 310 | 4850 |

