

Premium 3-stage solid OTR loader tire. Ideal for the most extreme OTR and construction applications. Extra-deep tread allows for 3 to 5 times longer tire life vs. pneumatic. Mounts on standard multi-piece earthmover rims.

- ▶ 3-stage, 100% rubber construction:
 - Ultra cut and wear-resistant tread compound
 - Heat-resistant cushion center compound
 - Pure rubber base compound
 - Internal hexagonal bead rings eliminate wheel slip
- ▶ Smooth tread available to maximize tire life
- ▶ Zero maintenance solid construction:
 - No flats due to punctures or sidewall damage
 - No routine air pressure checks
- ▶ Self-cleaning R4 tread pattern designed for maximum chunk resistance
- ▶ Aperture (AP) sidewall configuration designed to provide softer ride



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	TREAD	SIDEWALL	RIM	O.D.	S.W.	T.D.	L.C.C. (lbs/kg)		L.I.
				in	in	in	5 mph	10 mph	
				mm	mm	mm	10 kph	15 kph	
17.5-25	SM / TR / HT	ST	14.00	53	17.8	6.1	24700	17890	192A2
				1346	452	155	11200	8100	
		AP		53	17.8	6.1	22230	16100	188A2
				1346	452	155	10090	7300	
20.5-25	SM / TR / HT	ST	17.00	58.8	20.8	7.4	35300	25570	204A2
				1493	528	188	16010	11600	
		AP		58.8	20.8	7.4	30900	22380	
				1493	528	188	14020	10150	
23.5-25	SM / TR / HT	ST	19.50	64	23.5	8.6	44100	31950	212A2
				1625	597	218	20000	14500	
		AP		64	23.5	8.6	39700	28760	208A2
				1625	597	218	18000	13050	
26.5-25	SM / TR / HT	ST	22.00	68.4	27	9.5	53600	38830	219A2
				1737	686	241	24300	17600	
		AP		68.4	27	9.5	48100	34840	215A2
				1737	686	241	21800	15800	
29.5-25	SM / TR / HT	ST	25.00	73	29.7	10.4	66000	47810	226A2
				1854	754	264	30000	21700	
		AP		73	29.7	10.4	58400	42305	222A2
				1854	754	264	26500	19190	
18.00-25	SM	ST	13.00/2.5	64	19	8	38580	27950	207A2
				1625	483	203	17500	12680	
		AP		64	19	8	34170	24760	203A2
				1625	483	203	15500	11230	
30/75-29	SM / TR / HT	ST	25.00/3.5	75	30.6	10.4	69450	50310	228A2
				1905	777	264	31500	22820	
		AP		75	30.6	10.4	61730	44710	224A2
				1905	777	264	28000	20280	

