

Deep grooved tread design provides excellent traction in rigid dump truck applications. Ideal for applications requiring maximum road grip and high site TKPH/TMPH.

- ▶ Excellent traction in all off-road conditions
- ▶ Deep tread grooves provide cooler running tread for high site TKPH/TMPH
- ▶ Wide, square footprint distributes load for minimal haul road disturbance

- ▶ Reinforced bead, shoulder and sidewall for increased cut-resistance
- ▶ Heat-resistant undertread reduces tire temperature
- ▶ Multiple tread compound options target specific site requirements



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS

SIZE	RATING	TYPE	RIM	O.D.	S.W.	T.D.	TREAD COMPOUND	TMPH/TKPH	INFLATION PRESSURE	L.C.C. (LBS/KG)	L.I.
				in	in	32nds			psi	30 mph	
				mm	mm	mm			KPa	50 kph	
12.00R24	★★★	TT / TL	8.50V	48.7	12.4	39	Standard (S1)	-	102	9350	158B
				1238	315	31			700	4250	
14.00R24	★★★	TT	10.00W	55.2	15.4	46	Cut-Resistant (S2)	62/91	109	12800	169B
				1403	392	37	Standard (S1)	82/120	750	5800	
14.00R25	★★★	TT / TL	10.00/1.5	55.2	15.4	46	Cut-Resistant (S2)	62/91	109	12800	169B
				1403	392	37	Standard (S1)	82/120	750	5800	
18.00R25	★★	TL	13.00/2.5	65.8	19.4	62	Standard (S1)	-	102	20400	185B
				1671	494	49	Cut-Resistant (S2)	-	700	9250	
18.00R33	★★	TL	13.00/2.5	73.6	19.6	66	Cut-Resistant (S2)	118/173	102	24000	191B
				1869	497	52	Standard (S1)	146/213	700	10900	
							Heat-Resistant (S3)	171/249			
21.00R33	★★	TL	15.00/3.0	77.8	21.8	77	Cut-Resistant (S2)	151/221	102	30900	200B
				1975	554	61	Standard (S1)	187/273	700	14000	
							Heat-Resistant (S3)	218/318			
21.00R35	★★	TL	15.00/3.0	81	23	73	Cut-Resistant (S2)	151/221	102	32000	201B
				2057	584	58	Standard (S1)	187/273	700	14500	
							Heat-Resistant (S3)	218/318			
24.00R35	★★	TL	17.00/3.5	85.7	25.9	82	Cut-Resistant (S2)	200/292	102	40800	209B
				2177	658	65	Standard (S1)	247/361	700	18500	
							Heat-Resistant (S3)	288/421			
27.00R49	★★	TL	19.50/4.0	106.7	28.9	89	Ultra Cut-Resistant (S2UC)	257/375	102	60000	223B
							Cut-Resistant (S2)	319/465			
				2710	734	71	Standard (S1)	368/537	700	27250	
							Heat-Resistant (S3)	430/627			

