

Premium 3-stage solid skid steer tire. Ideal for the most extreme OTR and construction applications. Extra-deep tread allows for 3 to 5 times longer tire life vs. pneumatic.

- ▶ 3-stage, 100% rubber construction:
 - Ultra cut and wear-resistant tread compound
 - Heat-resistant cushion center compound
 - Pure rubber base compound
 - Internal steel ring reinforcement eliminates wheel slip
- ▶ Aperture (AP) sidewall configuration designed to provide soft ride
- ▶ Self-cleaning R4 tread pattern designed for maximum chunk resistance
- ▶ Smooth tread available to maximize tire life
- ▶ Zero maintenance solid construction:
 - No flats due to punctures or sidewall damage
 - No routine air pressure checks



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	ALT. SIZE	TREAD	SIDEWALL	RIM	O.D.	S.W.	T.D.	L.C.C. (lbs/kg)		L.I.
					in	in	in	5 mph	10 mph	
					mm	mm	mm	10 kph	15 kph	
10-16.5	31 x 10-20	SM	ST	7.5 x 20	31	10	1.7	7850	5690	152A2
					787	254	43	3550	2575	
		SM	AP	7.5 x 20	31	10	1.7	6950	5030	148A2
					787	254	43	3150	2280	
		R4	ST	7.5 x 20	31	10	1.7	7850	5690	152A2
					787	254	43	3550	2575	
		R4	AP	7.5 x 20	31	10	1.7	6950	5030	148A2
					787	254	43	3150	2280	
12-16.5	33 x 12-20	SM	ST	7.5 x 20	33	11	2.2	8800	6375	156A2
					838	279	56	4000	2900	
		SM	AP	7.5 x 20	33	11	2.2	7850	5690	152A2
					838	279	56	3550	2575	
		R4	ST	7.5 x 20	33	11	2.2	8800	6375	156A2
					838	279	56	4000	2900	
		R4	AP	7.5 x 20	33	11	2.2	7850	5690	152A2
					838	279	56	3550	2575	
14-17.5 15-19.5	36 x 14-20	R4	ST	7.5 x 20	36	13.7	2.9	9650	6990	159A2
					914	348	72	4375	3170	
		R4	AP	7.5 x 20	36	13.7	2.9	8550	6190	155A2
					914	348	72	3875	2800	
	40 x 14-20	R4	ST	10 x 20	40.0	14.0	128	14300	10350	173A2
					1016	356	102	6500	4705	
		R4	AP	10 x 20	40.0	14.0	128	12800	9265	169A2
					1016	355.6	102	5800	4200	

