

Standard E7 rib pattern maximizes ground contact and tread life while minimizing compaction.

- ▶ Low pressure, high flotation E7 pattern
- ▶ Paver compound resists chemical degradation
- ▶ Wear and cut-resistant tread compound



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (LBS/KG)	L.I.
				in	in	32nds	psi	5 mph	
				mm	mm	mm	KPa	10 kph	
14.00-20	12	TT	10.00W	47.8	14.6	15	58	12000	167A2
				1214	370	12	400	5450	
	14	TT	10.00W	47.8	14.6	15	69	13200	170A2
				1214	370	12	475	6000	
16.00-24	16	TL	10.00W	57.4	18.2	15	51	20400	185A2
				1458	462	12	350	9250	
18.00-25	16	TL	10.00/1.5	60.7	18.1	20	58	22700	189A2
				1543	460	16	400	10300	
	20	TL	10.00/1.5	60.7	18.1	20	69	25400	193A2
				1543	460	16	475	11500	
21.00-25	28	TL	15.00/3.0	66.4	22.2	22	83	36400	205A2
				1687	565	18	575	16500	

