

For loaders, graders, telehandlers and articulated dump trucks operating in soft underfoot conditions. Ideal for use in dirt, mud, snow and ice.

- ▶ Siped block pattern for maximum traction
- ▶ Self-cleaning tread with stone ejectors
- ▶ Wear and cut-resistant tread compound
- ▶ Approved for use in M+S (Mud and Snow) conditions



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



| SIZE | RATING | TYPE | RIM | O.D. | S.W. | T.D. | INFLATION PRESSURE | L.C.C. (Lbs/kg) | INFLATION PRESSURE | L.C.C. (Lbs/kg) | L.I. |
|----------|--------|------|-----------|------|------|-------|--------------------|-----------------|--------------------|-----------------|------------|
| | | | | in | in | 32nds | psi | 5 mph | psi | 30 mph | |
| | | | | mm | mm | mm | KPa | 10 kph | KPa | 50 kph | |
| 14.00R24 | ★ | TL | 10.00VA | 53.9 | 15.4 | 29 | 80 | 15200 | 69 | 9100 | 175A2/157B |
| | | | | 1368 | 390 | 23 | 550 | 6900 | 475 | 4125 | |
| 16.00R24 | ★ | TL | 10.00VA | 57.3 | 17 | 34 | 54 | 10200 | – | – | 161A8 |
| | | | | 1455 | 431 | 27 | 375 | 4625 | – | – | |
| 17.5R25 | ★★ | TL | 14.00/1.5 | 53.1 | 17.5 | 36 | 94 | 18700 | 76 | 12000 | 182A2/167B |
| | | | | 1348 | 445 | 29 | 650 | 8500 | 525 | 5450 | |
| 20.5R25 | ★★ | TL | 17.00/2.0 | 58.7 | 20 | 38 | 94 | 25400 | 76 | 16100 | 193A2/177B |
| | | | | 1490 | 511 | 30 | 650 | 11500 | 525 | 7300 | |
| 23.5R25 | ★★ | TL | 19.50/2.5 | 63.5 | 23.5 | 41 | 94 | 32000 | 76 | 20400 | 201A2/185B |
| | | | | 1613 | 597 | 33 | 650 | 14500 | 525 | 9250 | |
| 26.5R25 | ★★ | TL | 22.00/3.0 | 68.8 | 26.7 | 45 | 94 | 40800 | 76 | 25400 | 209A2/193B |
| | | | | 1748 | 678 | 36 | 650 | 18500 | 525 | 11500 | |
| 29.5R25 | ★★ | TL | 25.00/3.5 | 73.3 | 30.2 | 49 | 94 | 49400 | 76 | 30900 | 216A2/200B |
| | | | | 1862 | 766 | 39 | 650 | 22400 | 525 | 14000 | |
| 29.5R29 | ★★ | TL | 25.00/3.5 | 77.6 | 30.1 | 46 | 94 | 52000 | 76 | 33100 | 218A2/202B |
| | | | | 1971 | 765 | 37 | 650 | 23600 | 525 | 15000 | |

