

Light-duty E3/L3 lug pattern ideally suited to municipalities, small sand and aggregate operations as well as other smooth surface applications.

- ▶ Excellent traction in all off-road conditions
- ▶ Thick undertread for improved puncture resistance
- ▶ High-quality casing allows for excellent retreadability
- ▶ Wear and cut-resistant tread compound



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RATING	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (LBS/KG)	INFLATION PRESSURE	L.C.C. (LBS/KG)	L.I.
				in	in	32nds	psi	5 mph	psi	30 mph	
				mm	mm	mm	KPa	10 kph	KPa	50 kph	
15.5R25	★★	TL	12.00/1.3	50.2	15.3	29	94	15700	76	9900	176A2/160B
				1276	387.5	23	650	7100	525	4500	
17.5R25	★★	TL	14.00/1.5	53	17.6	31	94	18700	76	12000	182A2/167B
				1345	446	25	650	8500	525	5450	
20.5R25	★★	TL	17.00/2.0	58.5	20.5	34	94	25400	76	16100	193A2/177B
				1486	520	27	650	11500	525	7300	
23.5R25	★★	TL	19.50/2.5	63.1	23.8	38	94	32000	76	20400	201A2/185B
				1604	604	30	650	14500	525	9250	
26.5R25	★★	TL	22.00/3.0	68.7	26.5	43	94	40800	76	25400	209A2/193B
				1745	673	34	650	18500	525	11500	
29.5R25	★★	TL	25.00/3.5	73.8	29.4	46	94	49400	76	30900	216A2/200B
				1874	747	37	650	22400	525	14000	

