

Standard E3/L3 rock lug pattern combines excellent traction and high resistance to wear and cutting.

- ▶ Excellent traction in all off-road conditions
- ▶ Thick undertread for improved puncture resistance
- ▶ High-quality casing allows for excellent retreadability
- ▶ Wear and cut-resistant tread compound
- ▶ Wide, flat footprint profile for maximum stability and wear
- ▶ Increased net-to-gross for improved tread life



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RATING	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (LBS/KG)	INFLATION PRESSURE	L.C.C. (LBS/KG)	L.I.
				in	in	32nds	psi	5 mph	psi	30 mph	
				mm	mm	mm	KPa	10 kph	KPa	50 kph	
17.5R25	★★	TL	14.00/1.5	53	17.8	35	94	18700	76	12000	182A2/167B
				1346	452	28	650	8500	525	5450	
20.5R25	★★	TL	17.00/2.0	58.5	20.3	38	94	25400	76	16100	193A2/177B
				1485	515	30	650	11500	525	7300	
23.5R25	★★	TL	19.50/2.5	63.3	24	42	94	32000	76	20400	201A2/185B
				1609	610	33	650	14500	525	9250	
26.5R25	★★	TL	22.00/3.0	68.1	27	45	94	40800	76	25400	209A2/193B
				1731	685	36	650	18500	525	11500	
29.5R25	★★	TL	25.00/3.5	73.8	29.4	48	94	49400	76	30900	216A2/200B
				1874	747	38	650	22400	525	14000	

