

All-steel radial industrial tires designed for heavy loads and long cycle times in port and marina applications. Belt-stabilized tread provides better traction, longer tread life and lower heat buildup than bias construction tires.

- ▶ Belt-stabilized tread provides better traction and wear performance
- ▶ Extra-wide profile and reinforced sidewall for improved stability
- ▶ Tread pattern designed to maximize tread life
- ▶ Cut and wear-resistant compound
- ▶ High-quality casing allows for excellent retreadability



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RATING	TYPE	RIM	O.D.		S.W.		T.D.		INFLATION PRESSURE psi/KPa	L.C.C. (LBS/KG) 15 mph/25 kph	L.I.
				in	mm	in	mm	32nds	mm			
12.00R20	★★★	TT	8.50	45	1144	12.7	322	37	30	145/1000	20410/9230	176A5
12.00R24	★★★	TT	8.50	49.5	1256	12.4	314	37	30	145/1000	21450/9750	178A5
14.00R24	★★★	TT	10.00W	53.9	1369	14.9	378	50	40	145/1000	33020/14950	193A5
14.00R24	★★★	TL	10.00W	53.9	1369	14.9	378	50	40	145/1000	33020/14950	193A5

\* Load ratings for counterbalanced industrial cyclic application. Please contact a MAXAM representative for other applications.

