

Deep E4/L4 lug pattern combines excellent traction and high resistance to wear and cutting. Specifically designed to minimize vibration at haul speeds and provide the lowest cost-per-hour.

- ▶ Excellent traction in all off-road conditions
- ▶ Deep undertread for improved puncture resistance
- ▶ High-quality casing allows for excellent retreadability
- ▶ Wear and cut-resistant tread compound
- ▶ Wide, flat footprint profile for maximum stability and wear



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RATING	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (Lbs/Kg)	INFLATION PRESSURE	L.C.C. (Lbs/Kg)	L.I.
				in	in	32nds	psi	5 mph	psi	30 mph	
				mm	mm	mm	KPa	10 kph	KPa	50 kph	
23.5R25	★★	TL	19.50/2.5	63.9	24.0	68	94	32000	76	20400	201A2/185B
				1623	609	54	650	14500	525	9250	
26.5R25	★★	TL	22.00/3.0	69.5	26.7	75	94	40800	76	25400	209A2/193B
				1765	679	60	650	18500	525	11500	
29.5R25	★★	TL	25.00/3.5	73.7	29.7	79	94	49400	76	30900	216A2/200B
				1872	755	63	650	22400	525	14000	
775/65R29	★★	TL	25.00/3.5	68.7	30.4	68	91	45400	62	26800	213A2/195B
				1745	771	54	625	20600	425	12150	
800/80R29	★★	TL	27.00/3.5	79.4	31.4	84	-	-	65	37500	206B
				2017	798	67	-	-	450	17000	
875/65R29	★★	TL	27.00/3.5	73.5	34.1	76	91	56800	62	34200	221A2/203B
				1866	866	60	625	25750	425	15500	
875/65R29	★★★★	TL	27.00/3.5	in	in	32nds	psi	5 mph			227A2
				mm	mm	mm	KPa	10 kph			
				73.4	34	76	116	68000	-	-	
875/65R29	★★★★	TL	27.00/3.5	1864	863	60	800	30750	-	-	227A2
				in	in	32nds	psi	25 mph			
26.5R25	★★★★	TL	22.00/3.0	mm	mm	mm	KPa	40 kph			210A8
				68.7	26.6	75	116	41900	-	-	
26.5R25	★★★★	TL	22.00/3.0	1746	675	60	800	19000	-	-	210A8
				in	in	32nds	psi	25 mph			
29.5R25	★★★★	TL	25.00/3.5	73.9	30.5	79	116	50700	-	-	217A8
				mm	mm	mm	KPa	40 kph			
29.5R25	★★★★	TL	25.00/3.5	1876	774	63	800	23000	-	-	217A8
				in	in	32nds	psi	25 mph			

