

Deep E4/L4 lug pattern combines excellent traction and high resistance to wear and cutting. Specifically designed to maximize traction in loader applications and provide the lowest cost-per-hour.

- ▶ Excellent traction in all off-road conditions
- ▶ Deep undertread for improved puncture resistance
- ▶ High-quality casing allows for excellent retreadability
- ▶ Wear and cut-resistant tread compound
- ▶ Wide, flat footprint profile for maximum stability and wear



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RATING	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (LBS/KG)	INFLATION PRESSURE	L.C.C. (LBS/KG)	L.I.
				in	in	32nds	psi	5 mph	psi	30 mph	
				mm	mm	mm	KPa	10 kph	KPa	50 kph	
23.5R25	★★	TL	19.50/2.5	64.8	23.6	66	94	32000	76	20400	201A2/185B
				1645	601	52	650	14500	525	9250	
26.5R25	★★	TL	22.00/3.0	68.3	26.1	71	94	40800	76	25400	209A2/193B
				1736	662	56	650	18500	525	11500	
29.5R25	★★	TL	25.00/3.5	74.9	29.7	76	94	49400	76	30900	216A2/200B
				1903	755	60	650	22400	525	14000	
29.5R29	★★	TL	25.00/3.5	78.9	30.2	76	94	52000	76	33100	218A2/202B
				2005	766	60	650	23600	525	15000	
35/65R33	★★	TL	28.00/3.5	81.3	34.5	80	94	61500	76	38600	224A2/207B
				2066	877	64	650	28000	525	17500	
				in	in	32nds	psi	25 mph			
				mm	mm	mm	KPa	40 kph			
35/65R33	★★★★	TL	28.00/3.5	81.3	35.2	80	116	64000	-	-	225A8
				2066	893	64	800	29000	-	-	
29.5R29	★★★★	TL	25.00/3.5	78.7	30.0	76	116	53600	-	-	219A8
				1999	763	60	800	24300	-	-	

