

A versatile tread design allows flexibility in applications from smooth haul roads to rough and rocky terrain while providing maximum productivity.

- ▶ Excellent traction in all haul road conditions
- ▶ Deep tread grooves provide cooler running tread for high site TKPH/TMPH
- ▶ E4+ deep tread for longest tire life
- ▶ Wide, square footprint distributes load for minimal haul road disturbance
- ▶ Reinforced bead, shoulder and sidewall for increased cut-resistance
- ▶ Heat-resistant undertread reduces tire temperature
- ▶ Multiple tread compound options target specific site requirements



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RATING	TYPE	RIM	O.D.	S.W.	T.D.	TREAD COMPOUND	TMPH/TKPH	INFLATION PRESSURE		L.C.C. (LBS/KG)	L.I.
				in	in	32nds			psi	30 mph		
				mm	mm	mm			KPa	50 kph		
37.00R57	★★	TL	27.00/6.0	134.1	40	117	Cut-Resistant (S2)	453/660	102	113500	245B	
				3406	1016	93	Standard (S1)	552/805				
							Heat-Resistant (S3)	666/971	700	51500		
46/90R57	★★	TL	32.00/6.0	139.8	45.4	117	Cut-Resistant (S2)	514/750	102	139000	252B	
				3551	1154	93	Standard (S1)	617/900				
							Heat-Resistant (S3)	737/1075	700	63000		

