

A versatile tread with a stepped lug design for added protection from stone trapping. Allows flexibility in applications from smooth haul roads to rough and rocky terrain while providing maximum productivity.

- ▶ Excellent traction in all haul road conditions
- ▶ Deep tread grooves provide cooler running tread for high site TKPH/TMPH
- ▶ Optimized lower sidewall profile to prevent separations in that area
- ▶ Wide, square footprint distributes load for minimal haul road disturbance
- ▶ Reinforced bead, shoulder and sidewall for increased cut-resistance
- ▶ Heat-resistant undertread reduces tire temperature
- ▶ Multiple tread compound options target specific site requirements



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RATING	TYPE	RIM	O.D.	S.W.	T.D.	TREAD COMPOUND	TMPH/TKPH	INFLATION PRESSURE	L.C.C. (LBS/KE)	L.I.
				in	in	32nds			psi	30 mph	
				mm	mm	mm			KPa	50 kph	
46/90R57	★★	TL	32.00/6.0	140.6	45.2	121	Cut-Resistant (S2)	514/750	102	139000	252B
				3571	1148	96	Standard (S1)	617/900	700	63000	
							Heat-Resistant (S3)	737/1075			

