

Designed for heavy loads and long cycle times typical of demanding port applications.

- ▶ Extra-wide profile and reinforced sidewall for improved stability
- ▶ Multi-bead design to withstand extreme impact and shock loads
- ▶ Tread patterns designed to maximize tread life
- ▶ Cut and wear-resistant compound
- ▶ High-quality casing allows for excellent retreadability



**TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS**



SIZE	P.R.	TYPE	RIM	O.D.		S.W.		T.D.		INFLATION PRESSURE	L.C.C. (LBS/KG)	
				in	mm	in	mm	32nds	mm		15 mph/25 kph	
											LOAD WHEELS	STEER WHEELS
12.00-20 TR	20	TT	8.50	46.2	1173	12.4	315	25	20	145/1000	20410/9230	15700/7100
14.00-24 TR	28	TT	10.00W	53.4	1356	14.2	361	58	46	145/1000	28600/13000	22000/10000
14.00-24 TR	28	TL	10.00W	53.7	1364	14.8	375	58	46	145/1000	28600/13000	22000/10000
18.00-25 TR	40	TL	13.00/2.5	65.9	1673	20.5	520	71	56	145/1000	50180/22750	38600/17500
16.00-25 SM	32	TL	11.25/2.0	60.9	1547	16.9	429	64	51	145/1000	35880/16250	27600/12500
18.00-25 SM	40	TL	13.00/2.5	65.9	1674	19.9	505	68	54	145/1000	50180/22750	38600/17500
18.00-33 SM	40	TL	13.00/2.5	73.7	1872	19.6	498	69	55	145/1000	60710/27560	46700/21200

\* Load ratings for counterbalanced industrial cyclic application. Please contact a MAXAM representative for other applications.

