

MS906 > SKID STEER

Deep R4 tread pattern designed for skid steer, backhoe and telehandler applications.

- ▶ Full, flat profile with self-cleaning stepped tread improves performance
- ▶ Center tie bar reduces vibration during over-the-road driving

- ▶ Deep undertread for improved puncture resistance
- ▶ Special cut-resistant compound improves wear and reduces tread chunking



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.		S.W.	T.D.	INFLATION PRESSURE	L.C.C. (LBS/KG)				
				in	mm	in	mm		32nds	psi	5 mph	30 mph	
				mm	mm	mm	mm	KPa	10 kph	50 kph			
5.70-12	6	TL	4.50	22.4	569	5.7	18	60	1450	900			
						145	14	415	660	410			
23 x 8.50-12	6	TL	7JA	22.9	583	8.5	17	50	1820	1145			
						214	13	340	825	515			
	8	TL	7JA	22.9	583	8.5	17	65	2150	1355			
						214	13	450	975	615			
				12	TL	7JA	22.9	583	8.5	17	75	2680	1690
									214	13	515	1215	760
27 x 8.50-15	8	TL	7JA	26.9	682	8.7	18	60	2910	1820			
						221	14	415	1320	825			
27 x 10-12	14	TL	8.00G	27.6	701	10.4	24	100	7800	5040			
						254	19	690	3500	2250			
7.00-15	6	TL	5.50	29.9	760	7.8	21	60	3180	2015			
						198	16	415	1400	920			
	8	TL	5.50	29.9	760	7.8	21	70	3640	2290			
						198	16	480	1650	1030			
31 x 15.50-15	8	TL	13LB	31	787	15.1	30	45	4400	2760			
						384	23	310	2000	1250			
10-16.5	10	TL	8.25	30.2	768	10.7	21	75	4710	2950			
						271	16	515	2130	1330			
12-16.5	12	TL	9.75	32.8	834	13	25	80	6320	4030			
						331	20	550	2850	1830			
14-17.5	14	TL	10.50	36.2	920	14.2	33	80	8540	5360			
						360	26	550	3870	2430			
15-19.5	14	TL	11.75	40.2	1020	15.3	33	70	10060	6425			
						389	26	480	4560	2915			
	16	TL	11.75	40.2	1020	15.3	33	80	10880	6930			
						389	26	550	4935	3150			

