

Radial tire construction for skid steer applications, providing larger footprint, better stability, and higher traction than bias construction. Aggressive R4 tread pattern for applications requiring high traction.

- ▶ All-steel radial construction provides superior performance to bias
- ▶ Steel belts protect from punctures
- ▶ Wide tread design for increased flotation
- ▶ Wear and cut resistant compound
- ▶ Reinforced bead and sidewall for excellent stability



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	TYPE	RIM	O.D.	S.W.	T.D.	SPEED mph kph	INFLATION PRESSURE psi KPa	L.C.C. lbs kg	L.I.
			in	in	32nds				
			mm	mm	mm				
31x15.50R15	TL	13LB	31	15.1	30	5	45	4400	132A2
			787	384	23	10	310	2000	
10R16.5	TL	8.25	30.6	10.3	25	5	75	4680	134A2
			778	261	20	10	520	2120	
12R16.5	TL	9.75	32.9	11.9	30	5	80	6400	145A2
			835	301	23	10	550	2900	
14R17.5	TL	10.50	36.4	13.8	34	5	80	8550	155A2
			925	350	27	10	550	3875	
15R19.5	TL	11.75	40.1	15.3	33	5	70	10200	161A2
			1019	389	26	10	480	4625	

