

MAXAM MS938

R3 FLOTATION TIRE

The high flotation R3 pattern provides minimal ground compaction while providing excellent traction in the field.

- ▶ Excellent traction in all conditions
- ▶ Thick undertread for improved puncture resistance
- ▶ Low pressure minimizes soil disturbance
- ▶ Wear and cut-resistant tread compound



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Size	PR	Type	Rim (Rec.)	S.W.		O.D.		S.L.R.		Tread Depth 32nds mm	Weight lbs kg
					in	mm	in	mm	in	mm		
V346031	23.1-26	12	TL	DW20	23.1	587	61.8	1570	28	712	23 18	248 129
V346032	28L-26	16	TL	DW25	28.2	717	62.6	1590	28	712	34 27	375 170

MS938 LOAD AND INFLATION

Metric Size	LI / SS	Service Speed (mph/kph)	Cold Inflation Pressure	Maximum Cyclic Load		Road Transport
				Max speed 5mph (10km/h)	Max speed 10mph (15km/h)	Max speed 25mph (40km/h)
				psi	lbs	lbs
			kpa	kg	kg	kg
23.1-26	155A8	25/40	32	13400	12200	8550
			220	6100	5520	3875
28L-26	162A8	25/40	36	17000	15500	10500
			250	7710	7010	4750