

AGRIXTRA 85

- Standard sized R1W tire for varied farming operations
- Designed for agricultural machinery applications from tractors to harvesters



Metric Size	US Equivalent	L/SR	Weight (lbs)	T.D. (32nds)	GFP (sq in)
250/85R24	9.5R24	109A8/B	86	48	109
280/85R24	11.2R24	115A8/B	99	50	128
320/85R24	12.4R24	122A8/B	121	52	158
340/85R24	13.6R24	125A8/B	135	53	174
380/85R24	14.9R24	131A8/B	168	54	206
420/85R24	16.9R24	137A8/B	203	58	243
280/85R28	11.2R28	118A8/B	114	50	139
320/85R28	12.4R28	124A8/B	134	52	169
340/85R28	13.6R28	127A8/B	150	53	185
380/85R28	14.9R28	133A8/B	187	54	217
420/85R28	16.9R28	139A8/B	221	58	256
380/85R30	14.9R30	135A8/B	201	54	230
420/85R30	16.9R30	140A8/B	238	63	264
460/85R30	18.4R30	145A8/B	276	64	306
320/85R32	12.4R32	126A8/B	154	52	179
380/85R34	14.9R34	146A8/B	238	54	237
420/85R34	16.9R34	142A8/B	260	63	280
460/85R34	18.4R34	147A8/B	298	64	325
320/85R36	12.4R36	128A8/B	163	52	190
340/85R36	13.6R36	132A8/B	192	58	211
340/85R38	13.6R38	133A8/B	198	58	217
380/80R38	14.9R38	142A8/B	234	57	210
420/85R38	16.9R38	144A8/B	280	63	295
460/85R38	18.4R38	149A8/B	324	64	343
520/85R38	20.8R38	155A8/B	404	67	409
460/85R42	18.4R42	156A8/B	399	64	422
480/80R42	18.4R42	151A8/B	373	64	364
520/85R42	20.8R42	167D	485	67	370
480/80R46	18.4R46	158A8/B	417	64	336
520/85R46	20.8R46	158A8/B	496	69	449
480/80R50	18.4R50	176A8/B	549	66	358
480/95R50	-	164D	494	67	396

VF/SERIES					
VF480/95R50	-	170D	534	67	586

MAXAM

300 Rosewood Drive, Suite 102, Danvers, MA 01923 USA
 Phone.844-MAXAM-NA Fax.978-560-0624
 MAXAMTIRE.COM

RADIAL AG LIMITED WARRANTY

The below Limited Warranty and Adjustment Policy is a commitment of tire replacement under certain specified conditions as provided below. This warranty policy applies to all MAXAM radial agricultural tires as specified below and does not require the existence of a defect to be considered eligible for an adjustment.

Agricultural Use*	Stubble Damage or Field Hazard Coverage	Scraper Application Use*
Up to Eight Years	With Stubble Prevention Device	With Appropriate Weight and Air Pressure Settings
Year 1 100%*	Year 1 80%	Year 1 80%
Year 2 100%*	Year 2 60%	Year 2 60%
Year 3 80%	Year 3 40%	Year 3 40%
Year 4 70%	Year 4 20%	Year 4 20%
Year 5 60%	Year 5 No Coverage	Year 5 No Coverage
Year 6 50%	Year 6 No Coverage	Year 6 No Coverage
Year 7 30%	Year 7 No Coverage	Year 7 No Coverage
Year 8 20%	Year 8 No Coverage	Year 8 No Coverage

*100% FREE REPLACEMENT

See warranty document for policy details & conditions

PRODUCT ELIGIBILITY

All MAXAM brand radial agricultural tires manufactured and/or sold after January 1, 2018 and distributed by MAXAM per its identification code and production date. This policy applies to either the original owner, the user of the tires or the original purchaser of the agricultural equipment mounted with the tires. The MAXAM agricultural tires covered by this warranty policy belong to the following family of radial products: AGRIXTRA 85, AGRIXTRA 70, AGRIXTRA 65, AGRIXTRA XL, AGRIXTRA H, AGRIXTRA N, FLOTXTRA & AGILXTRA. For complete details on the MAXAM Radial Ag Limited Warranty, please visit our website: www.maxamtire.com or contact us at 1-844-MAXAM-NA.

**BUSINESS SOLUTIONS
 PROVIDER**

2024

MAXAM

PERFORMANCE ALL SEASON LONG

As a major global specialty tire manufacturer and distributor, MAXAM Tire has a reputation for delivering quality products at an exceptional value. MAXAM centers its core values around innovation and its commitment to enhanced tire performance.



SIMPLIFYING THE PROCESS

By providing the highest possible load index for every application, our range of performance-driven agricultural tires simplifies the buying process for farmers and growers.



SUPERIOR VALUE

MAXAM's radial agricultural tires are backed by a world-class warranty program to protect farmer's and grower's investment in our products.



PERFORMANCE DESIGN

MAXAM's radial tire construction ensures consistent tread ground contact, improving traction in the field and providing additional fuel savings in both hard and soft soil conditions.

RADIAL

AGRICULTURAL

S E R I E S

MAXAMTIRE.COM

AGRIXTRA 70

- Premium R1W traction tire designed for wide tread field applications
- Designed to carry the same load capacity at both 25 & 30 mph



Metric Size	Load Index/Speed Rating	Weight (lbs)	T.D. (32nds)	GFP (sq in)
260/70R16	109D	46	39	92
280/70R16	112D	55	40	93
280/70R18	114D	60	40	100
260/70R20	113D	55	39	98
280/70R20	116D	63	40	108
300/70R20	120D	69	42	124
360/70R24	122A8/B	139	50	158
380/70R24	125A8/B	157	52	174
420/70R24	130A8/B	181	53	201
480/70R24	138D	227	55	249
360/70R28	125A8	148	50	174
380/70R28	127A8/B	170	52	185
420/70R28	133A8/B	198	53	217
480/70R28	140A8/B	249	55	264
520/70R30	145A8/B	304	63	306
480/70R30	152D	309	60	241
480/70R34	155A8/B	333	60	263
520/70R34	148A8/B	332	63	332
480/70R38	145A8/B	319	57	306
520/70R38	150A8/B	366	63	354
580/70R38	155A8/B	444	71	409
620/70R42	166D	512	73	419
620/70R46	162D	575	73	547

AGRIXTRA XL

- Large volume R1W tire designed for high horsepower tractors and harvesters
- Designed to operate in the field, on the road and in scraping applications



Metric Size	Load Index/Speed Rating	Weight (lbs)	T.D. (32nds)	GFP (sq in)
600/65R28	154D	346	64	297
600/70R28	161D	392	68	382
600/70R30	158D	410	71	336
650/65R34	161D	487	73	433
650/75R38	169D	588	76	486
650/85R38	173D	767	78	514
710/70R38	171D	690	78	487
800/70R38	178D	908	78	594
710/70R42	173D	754	78	514
710/75R42	175D	785	78	546

VF/SERIES

VF600/65R28	159D	356	64	487
VF600/60R30	158D	332	64	461
VF600/70R30	165D	408	72	387
VF650/65R34	167D	487	73	433
VF710/60R38	171D	554	73	683
VF710/60R42	173D	605	74	676
VF710/70R42	179D	732	79	591
VF710/75R42	181D	783	79	801
VF650/85R42	180D	805	78	787
VF710/65R46	183D	743	76	691

AGRIXTRA 65

- Premium R1W traction tire designed for wide tread field applications
- Designed for low pressure operations to reduce soil compaction



Metric Size	Load Index/Speed Rating	Weight (lbs)	T.D. (32nds)	GFP (sq in)
440/65R24	128D	172	53	190
480/65R24	133D	198	54	217
540/65R24	140D	247	58	264
420/65R28	128D	170	52	190
440/65R28	131D	190	53	206
480/65R28	136D	216	54	236
540/65R28	142D	271	58	280
540/65R30	150D	318	63	265
540/65R34	145D	329	64	306
600/65R34	151D	375	66	364.1
540/65R38	147D	364	64	325
600/65R38	153D	401	66	385
650/65R38	166D	536	71	419
650/65R42	165D	531	73	449

VF/SERIES

VF650/65R42	170D	559	74	595
-------------	------	-----	----	-----

AGRIXTRA H

- Super volume R1W tire optimized for improved flotation and heavy loads up to 40 mph – load range D
- Steel-belt construction provides improved stability, traction, and puncture resistance
- Designed for both harvester and floater (spreader) applications




Metric Size	Load Index/Speed Rating	Weight (lbs)	T.D. (32nds)	GFP (sq in)
1000/50R25	172D	807	72	499
620/75R26	166A8/B	501	66	360
750/50R26	157D	346	50	326
750/65R26	166D	598	71	419
620/75R30	168D	478	74	433
650/75R32	172D	593	73	427
800/65R32	178D	761	73	509
800/70R32	181D	798	73	633
900/60R32	181D	871	72	560
1050/50R32	184D	959	59	611
1250/50R32	194A8/B	1246	76	1017
710/75R34	178D	681	74	578

VF/SERIES

VF500/85R24	163A8	284	49	403.5
-------------	-------	-----	----	-------

AGRIXTRA N

- R1W & R1 narrow tires designed for both field and road applications
- Optimized for high clearance or narrow crop applications
- Suitable for both tractors and self-propelled sprayers




Metric Size	Load Index/Speed Rating	Weight (lbs)	T.D. (32nds)	GFP (sq in)
420/90R30	147A8/B	265	62	243
270/95R32	136D	127	44	144
270/95R38	140D	150	44	158
320/90R46	148A8/B	233	54	195
340/90R46	150D	224	54	241
380/90R46	159A8/B	357	58	237
420/80R46	151A8/B	313	66	286
230/95R48	136D	137	42	138
270/95R48	144D	181	44	176
380/90R50	160A8/B	386	58	244
300/95R52	151D	234	47	224
320/90R54	151A8/B	264	54	212
380/90R54	152A8/B	332	62	296

VF/SERIES

VF380/90R46	173D	342	47	321
VF380/105R50	179D	445	53	382

AGILXTRA

- Radial implement I3 Flotation Tire
- Steel-belted construction provides high puncture resistance
- Aggressive tread pattern designed for high traction
- Excellent lateral stability for field work and roading
- Wear and cut resistant tread compound ideal for mixed use applications



Metric Size	Load Index/Speed Rating	Weight (lbs)	T.D. (32nds)	GFP (sq in)
560/60R22.5	165D	247	28	294
600/55R26.5	165D	311	31	269
650/55R26.5	169D	326	31	313
710/50R26.5	170D	373	31	342
500/60R22.5	155D	211	28	366
560/45R22.5	155D	194	28	217
710/45R22.5	165D	293	29	317

VF/SERIES

VF560/60R22.5	167D	267	28	309
VF600/55R26.5	173D	328	31	332

FLOTXTRA

- Radial implement I3 Flotation Tire
- Radial steel constructed implement tire designed for high loads and speeds up to 40 mph (65 kph) – load range D
- Optimized for both transportation or forage equipment
- High durability, long tread life and improved lateral stability



Metric Size	Load Index/Speed Rating	Weight (lbs)	T.D. (32nds)	GFP (sq in)
605/70R20.5 IMP	176F	603	23	261
500/60R22.5 IMP	155D	258	24	210
500/60R22.5 IMP	161D	258	24	210
560/45R22.5 IMP	152D	212	24	193
560/60R22.5 IMP	161D	298	24	251
560/60R22.5 IMP*	165D	298	24	251
600/50R22.5 IMP	159D	286	24	237
600/50R22.5 IMP	167D	286	24	237
710/35R22.5 IMP	157D	252	24	221
710/40R22.5 IMP	161D	321	24	251
600/55R26.5 IMP	165D	353	25	279
650/55R26.5 IMP	169D	381	25	315
710/50R26.5 IMP	170D	435	25	326
800/45R26.5 IMP	174D	481	25	364
600/60R30.5 IMP	173D	455	29	325
650/65R30.5 IMP	176D	534	29	385
710/50R30.5 IMP	173D	497	29	353
750/60R30.5 IMP	181D	603	30	448