




WHY CHOOSE OUR RADIAL SKID STEER & BACKHOE SERIES


Manufactured with all-steel-radial constructions, the radial skid steer & backhoe series deliver superior performance compared to the standard bias tires.

TREAD LIFE  **BIAS 300HRS / RADIAL 900HRS**

3x more tread life

DURABILITY/LOAD CAPACITY  **ALL-STEEL RADIAL CONSTRUCTION**

provides more strength




150%

savings in cost-per-hour

80%


fewer flats on job sites

RADIAL SKID STEER/BACKHOE SERIES



ALL-STEEL-RADIAL BUILT

Unrivaled performance and maximum puncture resistance



WIDE TREAD DESIGN

Provides increased flotation and traction in all conditions



HEAVY-DUTY CONSTRUCTION

Reinforced bead and sidewall for superior stability



MS901R



MS917R

MS906R

MS907R



MAXAM

- All-steel radial construction provides superior performance
- Steel belts for maximum puncture resistance
- Wide tread design for increased flotation
- Wear and cut-resistant compound
- Reinforced bead and sidewall for excellent stability

MS901R

SIZE	ALT SIZE	TYPE	RIM	O.D.	S.W.	T.D.	SPEED	INFLATION PRESSURE	L.C.C.	L.I.
				in	in	32nds	mph	psi	lbs	
				mm	mm	mm	kph	KPa	kg	
340/80R18	12.5/80R18	TL	W9	38.9	13.8	33	30	58	6000	143B
				987	351	26	50	400	2725	

MS906R

SIZE	TYPE	RIM	O.D.	S.W.	T.D.	SPEED	INFLATION PRESSURE	L.C.C.	L.I.
			in	in	32nds	mph	psi	lbs	
			mm	mm	mm	kph	KPa	kg	
31x15.50R15	TL	13LB	31	15.1	30	5	45	4400	132A2
			787	384	23	10	310	2000	
10R16.5	TL	8.25	30.6	10.3	25	5	75	4680	134A2
			778	261	20	10	520	2120	
12R16.5	TL	9.75	32.9	11.9	30	5	80	6400	145A2
			835	301	23	10	550	2900	
14R17.5	TL	10.50	36.4	13.8	34	5	80	8550	155A2
			925	350	27	10	550	3875	
15R19.5	TL	11.75	40.1	15.3	33	5	70	10200	161A2
			1019	389	26	10	480	4625	

MS907R

SIZE	TYPE	RIM	O.D.	S.W.	T.D.	SPEED	INFLATION PRESSURE	L.C.C.	L.I.
			in	in	32nds	mph	psi	lbs	
			mm	mm	mm	kph	KPa	kg	
10R16.5	TL	8.25	30.6	10.3	44	5	90	5680	141A2
			778	261	35	10	620	2575	
12R16.5	TL	9.75	32.7	11.8	44	5	90	6800	147A2
			830	300	35	10	620	3075	
14R17.5	TL	10.50	36.6	14.0	45	5	90	9100	157A2
			929	355	36	10	620	4125	

MS917R

SIZE	TYPE	RIM	O.D.	S.W.	T.D.	SPEED	INFLATION PRESSURE	L.C.C.	L.I.
			in	in	32nds	mph	psi	lbs	
			mm	mm	mm	kph	KPa	kg	
10R16.5	TL	8.25	30.6	10.3	39	5	90	5680	141A2
			778	261	31	10	620	2575	
12R16.5	TL	9.75	32.8	11.8	43	5	90	6800	147A2
			832	300	34	10	620	3075	

MS901R

MS906R

MS907R

MS917R



maxamtire.com