

All-steel radial industrial tires designed for heavy loads and long cycle times in port and marina applications. Belt-stabilized tread provides better traction, longer tread life and lower heat buildup than bias construction tires.

- ▶ Belt-stabilized tread provides better traction and wear performance
- ▶ Extra-wide profile and reinforced sidewall for improved stability
- ▶ Tread pattern designed to maximize tread life
- ▶ Cut and wear-resistant compound
- ▶ High-quality casing allows for excellent retreadability



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



| SIZE | RATING | TYPE | RIM | O.D. | | S.W. | | T.D. | | INFLATION PRESSURE psi/KPa | L.C.C. (LBS/KG) 15 mph/25 kph | L.I. |
|----------|--------|------|-----------|------|------|------|-----|-------|----|-------------------------------|----------------------------------|-------|
| | | | | in | mm | in | mm | 32nds | mm | | | |
| 10.00R20 | ★★★ | TT | 7.50 | 41.9 | 1064 | 11.2 | 285 | 44 | 35 | 145/1000 | 15210/6890 | 166A5 |
| 12.00R20 | ★★★ | TT | 8.50 | 44.8 | 1138 | 12.0 | 305 | 52 | 41 | 145/1000 | 20410/9230 | 176A5 |
| 12.00R24 | ★★★ | TT | 8.50 | 49.4 | 1255 | 12.5 | 317 | 52 | 41 | 145/1000 | 21450/9750 | 178A5 |
| 14.00R24 | ★★★ | TT | 10.00W | 55.6 | 1411 | 15.0 | 382 | 79 | 63 | 145/1000 | 33020/14950 | 193A5 |
| 14.00R24 | ★★★ | TL | 10.00W | 55.6 | 1411 | 15.0 | 382 | 79 | 63 | 145/1000 | 33020/14950 | 193A5 |
| 14.00R25 | ★★★ | TL | 10.00/1.5 | 55.6 | 1411 | 15.0 | 382 | 79 | 63 | 145/1000 | 33020/14950 | 193A5 |
| 16.00R25 | ★★★ | TL | 11.25 | 59.3 | 1506 | 17.2 | 436 | 68 | 54 | 145/1000 | 40170/18200 | 200A5 |
| 18.00R25 | ★★★ | TL | 13.00/2.5 | 64.8 | 1645 | 19.7 | 500 | 81 | 64 | 145/1000 | 50180/22750 | 207A5 |
| 18.00R33 | ★★★ | TL | 13.00/2.5 | 72.9 | 1851 | 19.8 | 503 | 86 | 69 | 145/1000 | 60710/27560 | 219A5 |

* Load ratings for counterbalanced industrial cyclic application. Please contact a MAXAM representative for other applications.

