



High performance three-stage solid resilient tire featuring a full-size tread profile for excellent traction, stability, and tire life.

Produced with EcoPoint<sup>3</sup> rubber compounding technology, providing exceptional resistance to wear and chunking, as well as minimal rolling resistance.

- ▶ Unique tread for an optimal combination of traction and tread life
- ▶ Smooth centerline design provides smooth ride, enhanced steering, and prevents chunking in aggressive applications
- ▶ Incorporates a superior center compound with unmatched heat-resistance and shock absorption for the most demanding industrial applications
- ▶ Widest footprint in its class for maximum lifting capabilities



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RIM	TYPE				O.D.		S.W.		L.C.C. (LBS/KG) 15 MPH/25 KPH	
		ST	SW	STNM	SWNM	in	mm	in	mm	LOAD WHEELS	STEER WHEELS
15x4.5-8	3.00D	•	•	•	•	15	381	4.5	114	2295/1040	1765/800
	3.25I	•	•	•	•	15	381	4.5	114	2295/1040	1765/800
16x6-8	4.33R	•	•	•	•	16.3	415	6	154	3210/1455	2470/1120
18x7-8	4.33R	•	•	•	•	18.1	461	6.1	156	4730/2145	3640/1650
5.00-8	3.00D	•	•	•	•	18.1	461	4.8	122	3120/1415	2405/1090
140/55-9	4.00E	•	•	•	•	15	381	5.1	129	2580/1170	1985/900
6.00-9	4.00E	•	•	•	•	20.9	531	5.5	141	4155/1885	3200/1450
21x8-9	6.00E	•	•	•	•	20.5	520	7.4	187	6075/2755	4675/2120
6.50-10	5.00F	•	•	•	•	22.7	576	6.6	166	5160/2340	3970/1800
23x9-10	6.50F	•	•	•	•	23.2	589	8	202	7595/3445	5840/2650
200/50-10	6.50F	•	•	•	•	18.1	461	7.7	195	5445/2470	4190/1900
7.00-12	5.00S	•	•	•	•	25.8	655	6.8	172	6440/2920	4940/2240
23x10-12	8.00G	•	•	•	•	23.2	589	9.3	236	8310/3770	6395/2900
27x10-12	8.00G	•	•	•	•	26.8	681	9.7	247	8600/3900	6610/3000
315/45-12	10.00G	•	•	•	•	23	584	11.2	284	9890/4485	7605/3450
7.00-15	5.50	•	•	•	•	29	737	7.2	182	7815/3545	6010/2725
	6.00	•	•	•	•	29	737	7.2	182	7815/3545	6010/2725
8.25-15	6.50	•	•	•	•	32.2	819	8.4	212	10470/4750	8050/3650
28x9-15	7.00	•	•	•	•	27.4	696	8.6	218	8600/3900	6615/3000
28x12.5-15	9.75	•	•	•	•	28.2	717	11.3	287	12180/5525	9370/4250



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RIM	TYPE				O.D.		S.W.		L.C.C. (LBS/KG) 15 MPH / 25 KPH	
		ST	SW	STNM	SWNM	in	mm	in	mm	LOAD WHEELS	STEER WHEELS
250-15	7.00	•	•	•	•	28.3	719	8.8	223	10470/4750	8045/3650
	7.50	•	•	•	•	28.3	719	8.8	223	10470/4750	8045/3650
300-15	8.00	•	•	•	•	32.2	819	10.1	256	12895/5850	9920/4500
355/65-15	9.75	•	•	•	•	32.2	819	12.3	313	17195/7800	13230/6000
400/60-15	11.00	•	•	•	•	32.4	822.3	13	331.4	19775/8970	15210/6900
10.00-20	7.00	•		•		40.7	1034	9.8	250	13230/6000	11025/5000
	7.50	•		•		40.7	1034	9.8	250	13230/6000	11025/5000
	8.00	•		•		40.7	1034	9.8	250	13230/6000	11025/5000
12.00-20	8.00	•		•		43.2	1098	11.1	282	16660/7560	13890/6300
	8.50	•		•		43.2	1098	11.1	282	16660/7560	13890/6300
	10.00	•		•		43.2	1098	11.1	282	16660/7560	13890/6300
12.00-24	8.50	•				47.4	1203	11.8	299	17720/8040	14770/6700
	10.00	•				47.4	1203	11.8	299	17720/8040	14770/6700
14.00-24	10.00	•				52.4	1331	12.9	328	24470/11100	20390/9250
14.00-25	10.00	•				52.4	1331	12.9	328	24470/11100	20390/9250
	11.25	•				52.4	1331	12.9	328	24470/11100	20390/9250
16.00-25	11.25	•				57.3	1456	16.1	408	35880/16250	27600/12500
18.00-25	13.00	•				64	1625	18.5	471	50180/22750	38600/17500

