

Modified R1 tread pattern for excellent traction and flotation in soft underfoot conditions.

- ▶ Tread design optimized with self-cleaning mud breakers
- ▶ Center tie bar reduces vibration during over-the-road driving

- ▶ Deep undertread for improved puncture resistance
- ▶ Wear and cut-resistant compound



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	POSITION	L.C.C. (Lbs/Kg)		L.I.
				in	in	32nds	psi		5 mph	25 mph	
				mm	mm	mm	KPa		10 kph	40 kph	
12.5/80-18	12	TL	9.00	38.8	13.4	26	58	-	7500	6000	143A8
				986	340	21	400		3400	2725	
15.5/80-24 (400/80-24)	12	TL	13.00	50	15.5	35	44	-	11550	8250	154A8
				1270	394	28	300		5220	3750	
	14	TL	13.00	50	15.5	35	51	-	12320	8800	156A8
				1270	394	28	350		5600	4000	
	16	TL	13.00	50	15.5	35	58	-	13510	9650	159A8
				1270	394	28	400		6100	4375	
16.5/85-24	12	TL	13.00	52	16.4	35	40	FREE	14700	10500	162A8
				6670	4750						
	12	TL	13.00	1321	417	28	275	DRIVE	10360	7400	150A8
				4700	3350						
	14	TL	13.00	52	16.4	35	48	FREE	15960	11400	165A8
				7240	5150						
	14	TL	13.00	1321	417	28	330	DRIVE	11270	8050	153A8
				5100	3650						
	16	TL	13.00	52	16.4	35	55	FREE	17220	12300	168A8
				7810	5600						
	16	TL	13.00	1321	417	28	380	DRIVE	12320	8800	156A8
				5600	4000						
16.5/85-28	10	TL	W13	54.9	15.2	35	33	FREE	12320	8800	156A8
				5600	4000						
	10	TL	W13	1394	386	28	225	DRIVE	8610	6150	144A8
				3900	2800						

