

Modified R4 tread pattern for excellent traction and flotation in soft underfoot conditions.

- ▶ Tread design optimized with self-cleaning mud breakers
- ▶ Center tie bar reduces vibration during over-the-road driving
- ▶ Deep undertread for improved puncture resistance
- ▶ Wear and cut-resistant compound



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (Lbs/kg)		L.I.	
				in	in	32nds		psi	5 mph		25 mph
				mm	mm	mm		KPa	10 kph		40 kph
18.4-26 (480/80-26)	12	TL	W16L	56.3	18.8	36	36	11000	8800	156A8	
				1430	478	29	250	5000	4000		
	16	TL	W16L	56.3	18.8	36	45	13125	10500	162A8	
				1430	478	29	310	5940	4750		
16.9-28 (440/80-28)	12	TL	W15L	55.5	17.2	34	38	9815	7850	152A8	
				1410	437	27	260	4440	3550		
	14	TL	W15L	55.5	17.2	34	44	10690	8550	155A8	
				1410	437	27	300	4840	3875		
16.9-30 (420/85-30)	12	TL	W15L	57.5	17.1	34	34	10060	8050	153A8	
				1461	434	27	235	4560	3650		
	14	TL	W15L	57.5	17.1	34	45	11000	8800	156A8	
				1461	434	27	310	5000	4000		
18.4-30 (460/85-30)	12	TL	W16L	60.2	18.5	36	36	11690	9350	158A8	
				1529	470	29	250	5310	4250		
	14	TL	W16L	60.2	18.5	36	42	12375	9900	160A8	
				1529	470	29	290	5625	4500		

