

Modified R4 tread pattern for applications combining high off-road traction and excellent on road performance.

- ▶ Tread design optimized with self-cleaning mud breakers
- ▶ Center tie bar reduces vibration during over-the-road driving
- ▶ Deep undertread for improved puncture resistance
- ▶ Wear and cut-resistant compound
- ▶ Increased net-to-gross for long tread life



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (Lbs/Kg)		L.I.
				in	in	32nds		psi	5 mph	
				mm	mm	mm	KPa	10 kph	40 kph	
17.5L-24 (460/70-24)	10	TL	W15L	48.8	17.5	33	32	7690	6150	144A8
				1240	445	26	220	3500	2800	
	12	TL	W15L	48.9	17.5	33	38	8940	7150	149A8
				1241	445	26	26	4060	3250	
	16	TL	W15L	48.9	17.5	33	46	11000	9650	159A8
				1241	445	26	320	5000	4375	
19.5L-24 (500/70-24)	12	TL	W16L	51.7	19.5	34	33	9500	7600	151A8
				1314	495	28	225	4310	3450	
	16	TL	W16L	51.7	19.5	34	42	11375	11000	164A8
				1314	495	28	290	5150	5000	
21L-24	12	TL	W18	54.3	21	35	32	10690	8550	155A8
				1378	533	28	220	4840	3875	

