

Extra-deep, aggressive L5 tread pattern designed for skid steer, backhoe and telehandler applications.

- ▶ Full, flat profile with self-cleaning stepped tread improves performance
- ▶ Center tie bar reduces vibration during over-the-road driving
- ▶ Deep undertread for improved puncture resistance
- ▶ Special cut-resistant compound improves wear and reduces tread chunking
- ▶ Increased net-to-gross for maximum tread life and lowest cost-per-hour



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.		T.D.	INFLATION PRESSURE		L.C.C. (LBS/KG)
				in	in	32nds	psi	5 mph	
				mm	mm	mm	KPa	10 kph	
23x8.50-12	8	TL	7JA	22.6	8.4	35	65	2150	
				574	213	28	450	975	
27x8.50-15	10	TL	7JA	27	8.7	38	75	3300	
				686	221	30	515	1500	
10-16.5	14	TL	8.25	31.3	10.9	44	105	5680	
				795	278	35	620	1800	
12-16.5	14	TL	9.75	33.1	13	44	90	6780	
				842	330	35	620	3075	
14-17.5	16	TL	10.50	36.8	14.1	45	90	9100	
				935	357	36	620	4125	
12.5/80-18	14	TL	W9	38	12	47	62	8260	
				965	306	37	425	3745	
	16	TL	W9	38	12	47	70	8940	
				965	306	37	480	4055	
19.5L-24	14	TL	W16L	51.1	19.3	48	38	10310	
				1298	490	38	265	4680	
21L-24	16	TL	W18	54.1	20.6	50	40	12375	
				1374	523	40	275	5615	
16.9-28	14	TL	W15L	55.5	17.7	48	45	10690	
				1410	450	38	310	4850	

