

Low-profile, reinforced tires designed for aerial platform lift applications with high stability requirements. High-traction R4 pattern provides excellent performance in all ground conditions.

- ▶ Self-cleaning, aggressive R4 pattern with deep lug grooves provides excellent traction and handling
- ▶ Extra-thick sidewall gauge for exceptional resistance to cutting
- ▶ Square shoulder design and wide footprint for maximum safety and stability in heavily loaded conditions



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	PR	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C.	L.I.
				in	in	32nds	psi	5 mph	
				mm	mm	mm	KPa	10 mph	
15-625	16	TL	24.50	40.4	15.7	26	100	12300	168A2
				1027	399	21	690	5600	
18-625	16	TL	24.50	40.5	17.4	26	100	15200	175A2
				1029	441	21	690	6900	
315/55D20	12	TL	20.00	32.8	12.4	24	80	7400	150A2
				833	316	19	550	3350	
355/55D625	14	TL	24.50	36.9	13.8	25	75	8800	156A2
				937	350	20	520	4000	
385/65D22.5	16	TL	22.50	42.8	16.1	26	100	12300	168A2
				1087	410	21	690	5600	
445/50D710	18	TL	28.00	45.6	17.6	28	100	16100	177A2
				1160	448	22	690	7300	

