

For use in the most severe applications where traction and long tread life are required.

- ▶ Specialized mining compound for increased cut and impact resistance
- ▶ Extra-deep L5 offset lug pattern combines excellent traction and high resistance to wear in all off-road conditions
- ▶ Deep undertread for improved puncture resistance
- ▶ Reinforced bead, shoulder and sidewall for increased cut-resistance



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RATING	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (Lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	
17.5R25	★★	TL	14.00/1.5	55.4	17	82	94	18700	182A2
				1408	433	65	650	8500	
18.00R25	★★★★	TL	13.00/2.5	66	19.9	100	123	37500	206A2
				1676	506	79	850	17000	
20.5R25	★★	TL	17.00/2.0	60.9	20.9	91	94	25400	193A2
				1547	532	72	650	11500	
23.5R25	★★	TL	19.50/2.5	65.4	23.9	101	94	32000	201A2
				1662	608	80	650	14500	
26.5R25	★★	TL	22.00/3.0	70.7	26.6	110	94	40800	209A2
				1796	675	87	650	18500	
29.5R25	★★	TL	25.00/3.5	75.9	30.4	117	94	49400	216A2
				1928	772	93	650	22400	
29.5R29	★★	TL	25.00/3.5	79.2	30.7	123	94	52000	218A2
				2011	779	98	650	23600	
35/65R33	★★	TL	28.00/3.5	81.4	34.9	120	94	61500	224A2
				2068	886	95	650	28000	
26.5R25	★★★★	TL	22.00/3.0	70.7	26.6	109	116	46700	214A2
				1796	675	87	800	21200	
35/65R33	★★★★	TL	28.00/3.5	81.4	34.9	120	116	71500	229A2
				2068	886	95	800	32500	
45/65R45	★★★★	TL	36.00/4.5	107.6	44.3	146	116	132500	250A2
				2734	1124	116	800	60000	