

High net-to-gross pattern provides extremely low wear rates while engineered tread grooves allow for exceptional traction and heat-resistance.

- ▶ Excellent traction in many haul roads conditions
- ▶ Strong all-steel casing to reduce cuts and punctures; increasing the casing durability
- ▶ High lug-to-void ratio for improved wear and impact protection
- ▶ Deep tread grooves provide cooler running tread
- ▶ Strategically placed stone ejectors provide maximum protection from stone trapping
- ▶ Optimized base compound enables high speed operation with low heat build-up



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



| SIZE     | RATING | TYPE | RIM       | O.D.  | S.W. | T.D.  | TREAD COMPOUND             | TMPH/TKPH | INFLATION PRESSURE |        | L.C.C. (LBS/KG) | L.I. |
|----------|--------|------|-----------|-------|------|-------|----------------------------|-----------|--------------------|--------|-----------------|------|
|          |        |      |           | in    | in   | 32nds |                            |           | psi                | 30 mph |                 |      |
|          |        |      |           | mm    | mm   | mm    |                            |           | KPa                | 50 kph |                 |      |
| 27.00R49 | ★★     | TL   | 19.50/4.0 | 106.1 | 29   | 82    | Ultra Cut-Resistant (S2UC) | 250/365   | 102                | 60000  | 223B            |      |
|          |        |      |           |       |      |       | Cut-Resistant (S2)         | 311/454   |                    |        |                 |      |
|          |        |      |           | 2694  | 737  | 65    | Standard (S1)              | 380/554   | 700                | 27250  |                 |      |
|          |        |      |           |       |      |       | Heat-Resistant (S3)        | 444/648   |                    |        |                 |      |
| 33.00R51 | ★★     | TL   | 24.00/5.0 | 120.3 | 36.5 | 118   | Ultra Cut-Resistant (S2UC) | 298/435   | 102                | 85400  | 235B            |      |
|          |        |      |           |       |      |       | Cut-Resistant (S2)         | 374/545   |                    |        |                 |      |
|          |        |      |           | 3056  | 926  | 94    | Standard (S1)              | 446/650   | 700                | 38750  |                 |      |
|          |        |      |           |       |      |       | Heat-Resistant (S3)        | 514/750   |                    |        |                 |      |

